Lifting Solutions Group
Axel Johnson International

Open Body Turnbuckles Jaw - Jaw

Product information



General:
- Generally to ASTM F 1145-92
- Standard hot dip galvanized.
- Factory supplied with lock nuts.
- Proof load 2.5 x WLL.
- Straight or in-line pull only.
- Drop forged high tensile steel.
- MBL equals or over 5x WLL

... *Read more*


Mennens Belgium
sales@mennensbelgium.be
+32 (0)3 253 23 23

© November 2026 - All Rights Reserved

MENNENS | Lifting Solutions Group
Axel Johnson International

Open Body Turnbuckles Jaw - Jaw

Blueprint



Mennens Belgium
sales@mennensbelgium.be
+32 (0)3 253 23 23

© November 2026 - All Rights Reserved

MENNENS | Lifting Solutions Group
Axel Johnson International

Open Body Turnbuckles Jaw - Jaw

Technical data

Part code	WLL ton	Thread mm	Thread Inch	Take up mm	L min. mm	L max. mm	A mm	P mm	U mm	W mm	Weight kg
422100230200	0.23	6.35	1/4	102	175	277	121	6	15	11	0.16
422100360200	0.36	7.94	5/16	114	212	314	138	6	22	13	0.24
422100540200	0.54	9.53	3.8	152	258	410	181	8	22	14	0.37
422100100200	1	12.7	1/2	152	292	470	190	10	27	16	0.71
422100100205	1	12.7	1/2	229	368	622	266	10	27	16	0.79
422100100206	1	12.7	1/2	305	445	775	343	10	27	15	1.09
422100160200	1.59	15.9	5/8	152	325	509	200	13	33	20	1.23
422100160205	1.59	15.9	5/8	229	401	662	276	13	33	20	1.56
422100160206	1.59	15.9	5/8	305	478	814	353	13	33	20	1.77
422100240200	2.36	19.1	3/4	152	356	546	210	16	38	24	1.86
422100240205	2.36	19.1	3/4	229	432	699	286	16	38	24	2.48
422100240206	2.36	19.1	3/4	305	508	851	362	16	38	24	2.98
422100240207	2.36	19.1	3/4	457	660	1,156	514	16	38	24	3.64
422100330200	3.27	22.2	7/8	305	543	892	370	19	44	29	3.71
422100330205	3.27	22.2	7/8	457	695	1,197	523	19	44	29	4.89
422100450205	4.54	25.4	1	152	425	628	228	22	52	34	4.62
422100450207	4.54	25.4	1	305	577	933	380	22	52	34	5.53
422100450206	4.54	25.4	1	457	729	1,237	532	22	52	34	6.87
422100450200	4.54	25.4	1	610	882	1,542	685	22	52	34	8.2
422100690200	6.89	31.8	1-1/4	305	644	1,012	384	28	71	44	9.34
422100690205	6.89	31.8	1-1/4	457	796	1,317	537	28	71	44	11.2
422100690206	6.89	31.8	1-1/4	610	948	1,622	689	28	71	44	12.8
422100970200	9.71	38.1	1-1/2	305	673	1,073	400	35	71	52	13.9
422100970205	9.71	38.1	1-1/2	457	826	1,359	553	35	71	52	16.7
422100970206	9.71	38.1	1-1/2	610	978	1,664	705	35	71	52	18.9
422101270200	12.7	44.5	1-3/4	457	899	1,356	568	41	86	66	24.5
422101270205	12.7	44.5	1-3/4	610	1,051	1,661	721	41	86	66	28.7
422101680200	16.8	51	2	610	1,157	1,766	738	51	94	66	46.5
422102720200	27.2	63.5	2-1/2	610	1,244	1,854	789	57	113	76	75
422103400200	34	70	2-3/4	610	1,289	1,899	788	70	106	92	90

Mennens Belgium
sales@mennensbelgium.be
+32 (0)3 253 23 23

© November 2026 - All Rights Reserved