

## Open Body Turnbuckles Jaw - Oval Eye



### Product information

**General:**

- Standard hot dip galvanized.
- Factory supplied with lock nuts.
- Proof load 2.5 x WLL.
- Straight or in-line pull only.
- Drop forged high tensile steel.
- MBL equals 5x WLL.

Part code	WLL ton	Thread mm	Thread Inch	Take up mm	L min. mm	L max. mm	A mm	I mm	K mm	L	P mm	U mm	W mm	Weight kg
11.51400250412	0.23	6.35	1/4	102	187	288	121	6	9	20	6	15	11	0.14
11.51400250412	0.36	7.94	5/16	114	221	348	138	8	11	24	6	22	13	0.23
11.51400330612	0.54	9.53	3/8	152	275	427	181	9	13	28	8	22	14	0.36
11.51400500612	1	12.7	1/2	152	312	490	190	11	18	37	10	27	16	0.68
11.51400500912	1	12.7	1/2	229	388	642	266	11	18	37	10	27	16	0.78
11.51400501212	1	12.7	1/2	305	465	795	343	11	18	37	10	27	16	0.94
11.51400620612	1.59	15.9	5/8	152	349	533	200	13	22	44	13	33	20	1.07
11.51400620912	1.59	15.9	5/8	229	425	686	276	13	22	44	13	33	20	1.44

11.51400621212	1.59	15.9	5/8	305	501	838	353	13	22	44	13	33	20	1.64
11.51400750612	2.36	19.1	3/4	152	390	575	210	16	25	53	16	38	24	1.81
11.51400750912	2.36	19.1	3/4	229	470	730	286	16	25	53	16	38	24	2.15
11.51400751212	2.36	19.1	3/4	305	540	880	362	16	25	53	16	38	24	2.69
11.51400751812	2.36	19.1	3/4	457	691	1,186	514	16	25	53	16	38	24	3.18
11.51400871212	3.27	22.2	7/8	305	567	917	307	19	32	60	19	44	29	3.79
11.51400871812	3.27	22.2	7/8	457	720	1,220	523	19	32	60	19	44	29	4.42
11.51401000612	4.54	25.4	1	152	470	670	228	23	36	76	22	52	34	4.05
11.51401001212	4.54	25.4	1	305	620	970	380	23	36	76	22	52	34	5.08
11.51401001812	4.54	25.4	1	457	680	1,260	532	23	36	76	22	52	34	6.03
11.51401002412	4.54	25.4	1	610	930	1,580	685	23	36	76	22	52	34	7.71
11.51401251212	6.89	31.8	1-1/4	305	690	1,050	384	29	46	90	28	71	44	8.81
11.51401251812	6.89	31.8	1-1/4	457	850	1,350	537	29	46	90	28	71	44	11
11.51401252412	6.89	31.8	1-1/4	610	990	1,650	689	29	46	90	28	71	44	12.9
11.51401501212	9.71	38.1	1-1/2	205	725	1,105	400	32	54	103	35	71	52	13.1
11.51401501812	9.71	38.1	1-1/2	457	880	1,410	553	32	54	103	35	71	52	15.9
11.51401502412	9.71	38.1	1-1/2	610	1,030	1,715	705	32	54	103	35	71	52	17.8
11.51401751812	12.7	44.5	1-3/4	457	950	1,410	568	38	60	117	41	86	66	24.4
11.51401752412	12.7	44.5	1-3/4	610	1,100	1,711	721	38	60	117	41	86	66	27.5
11.51402002412	16.8	51	2	610	1,235	1,845	738	45	68	146	51	94	66	40.4
11.51402502412	27.2	63.5	2-1/2	610	1,315	1,925	789	51	79	165	57	113	76	68
11.51402752412	34	70	2-3/4	610	1,370	1,980	789	57	82	177	70	106	92	83

**Blueprint**

