



DBI-SALA® Sealed-Blok™ Self-Retracting Lifeline

Product information

The 3M™ DBI-SALA® Sealed-Blok™ Self-Retracting Lifeline is engineered to endure the toughest environments. Its rugged design features corrosion-resistant materials, including stainless steel end-plates and aluminum housing, making it ideal for challenging applications such as oil and gas operations, confined spaces, saltwater and contaminated environments, and sewage facilities. With years of proven field service, Sealed-Blok™ provides reliable, high-quality fall protection.

For work at height or in confined spaces within extreme environments, dependable self-retracting lifelines (SRLs) are essential to a comprehensive fall protection solution. The 3M™ DBI SALA® Sealed-Blok™ SRL is built for durability with corrosion-resistant components, stainless steel end plates, and aluminum housing to withstand severe conditions. With its IP69K-rated housing that fully seals dynamic components, Sealed-Blok™ prevents water and particles from entering—even during continuous submersion. The lifeline extends and retracts automatically, allowing users to move freely within a designated working area. If a fall occurs, a speed-sensing brake system activates to stop the fall, reducing impact forces on the user to safe levels.

Highlights:

- Use the 3M™ DBI-SALA® Sealed-Blok™ SRL for working at height applications in some of the toughest environments
- Pivoting anchorage loop centres the load
- Sealed Design (meets IP69 rating) ensures safe, efficient operation under all working conditions
- 5 mm diameter stainless steel wire rope for corrosion resistance
- 2,267 kg rated handle
- Equipped with an integrated carrying handle to assist in transporting the SRL to job sites
- Swiveling self-locking snap hook with impact indicator
- Pivoting anchorage connector loop
- Available in multiple configurations, lifeline lengths and material types
- Anti-ratcheting design - stays locked on rigid and non-rigid horizontal lifeline anchors
- IP 69K ingress protection rating
- Impact Indicator

Material: Housing: Aluminium and stainless steel

Marking: According to standard

Standard: EN 360

Length m	Type	Karabiner	Block weight kg	Max user weight kg
40	3,400,972	16 kN gate rated double action steel snap hook, with swivel	27	140
53	3,400,658	16 kN gate rated double action steel snap hook, with swivel	56,5	140
53	3,400,656	16 kN gate rated double action steel snap hook, with swivel	56,5	140
4.5	3,400,830	16 kN gate rated double action steel snap hook, with swivel	5,5	140
4.5	3,400,828	16 kN gate rated double action steel snap hook, with swivel	5,5	140
9	3,400,803	16 kN gate rated double action steel snap hook, with swivel	9	140
9	3,400,805	16 kN gate rated double action steel snap hook, with swivel	9	140
15	3,400,950	16 kN gate rated double action steel snap hook, with swivel	14,5	140
15	3,400,951	16 kN gate rated double action steel snap hook, with swivel	14,5	140
25	3,400,866	16 kN gate rated double action steel snap hook, with swivel	20	140
25	3,400,867	16 kN gate rated double action steel snap hook, with swivel	20	140
40	3,400,971	16 kN gate rated double action steel snap hook, with swivel	27	140