



## Sealed Blok® with RSQ® Rescue Function

### Product information

Sealed Blok, for heavy environments. The RSQ® system for rescue allows for either automatic rescue after a fall, or manually assisted rescue, the latter operated from above or from below.

Sealed design meets IP68 sealed rating.

Steel cable in stainless or galvanized. Please specify.

#### Extra features for safety / comfort / lower cost of ownership:

- Fall impact indicator on karabiner.
- Swivel prevents cable from too much twist.
- Cable replacement, on location, without opening block.

**Material:** Housing: Aluminium

**Note:** In case of blocks with rescue winch: the winch is only for rescue. For general hoisting purposes with material loads, or with persons, winches are needed with dedicated certifications.

Length m	Type	Karabiner	Block weight kg	EN standard	Max user weight kg	Rescue winch
25	3,400,892	16 kN gate rated double action steel snap hook, with swivel	20	360, 341	140	-
25	3,400,917	16 kN gate rated double action steel snap hook, with swivel	20	360, 341, 1496	140	+
15	3,400,961	16 kN gate rated double action steel snap hook, with swivel	14,5	360, 341	140	-
15	3,400,944	16 kN gate rated double action steel snap hook, with swivel	14,5	360, 341, 1496	140	+
25	3,400,916	16 kN gate rated double action steel snap hook, with swivel	20	360, 341, 1496	140	+