

Sealed Blok® with RSQ® Rescue Function

Product information



Sealed Blok, for heavy environments. The RSQ® system for rescue allows for either automatic rescue after a fall, or manually assisted rescue, the latter operated from above or from below.

Sealed design meets IP68 sealed rating.

Steel cable in stainless or galvanized. Please specify.

Extra features for safety / comfort / lower cost of ownership:

- Fall impact indicator on karabiner.
- Swivel prevents cable from too much twist.
- Cable replacement, on location, without opening block.

[... Read more](#)

Material: Housing: Aluminium

Note: In case of blocks with rescue winch: the winch is only for rescue. For general hoisting purposes with material loads, or with persons, winches are needed with dedicated certifications.

Sealed Blok® with RSQ® Rescue Function

Technical data

| Length m | Type | Karabiner | Block weight kg | EN standard | Max user weight kg | Rescue winch |
|-------------|-----------|---|--------------------|----------------|-----------------------|--------------|
| 25 | 3,400,892 | 16 kN gate rated double action steel snap hook, with swivel | 20 | 360, 341 | 140 | - |
| 25 | 3,400,917 | 16 kN gate rated double action steel snap hook, with swivel | 20 | 360, 341, 1496 | 140 | + |
| 15 | 3,400,961 | 16 kN gate rated double action steel snap hook, with swivel | 14,5 | 360, 341 | 140 | - |
| 15 | 3,400,944 | 16 kN gate rated double action steel snap hook, with swivel | 14,5 | 360, 341, 1496 | 140 | + |
| 25 | 3,400,916 | 16 kN gate rated double action steel snap hook, with swivel | 20 | 360, 341, 1496 | 140 | + |