Sealed Blok® with RSQ® Rescue Function

Product information

Sealed Blok, for heavy environments. The RSQ® system for rescue allows for either automatic rescue after a fall, or manually assisted rescue, the latter operated from above or from below.

Sealed design meets IP68 sealed rating.

Steel cable in stainless or galvanized. Please specify.

Extra features for safety / comfort / lower cost of ownership:

- Fall impact indicator on karabiner.
- Swivel prevents cable from too much twist.
- Cable replacement, on location, without opening block.

... *Read more*

Material: Housing: Aluminium
Note: In case of blocks with rescue winch: the winch is only for rescue. For general hoisting purposes with material loads, or with persons, winches are needed with dedicated certifications.

Mennens Belgium
sales@mennensbelgium.be
+32 (0)3 253 23 23

© November 2026 - All Rights Reserved

Sealed Blok® with RSQ® Rescue Function

Technical data

Part code	Length m	Type	Karabiner	Block weight kg	EN standard	Max user weight kg	Rescue winch
822102500442	25	3,400,892	16 kN gate rated double action steel snap hook, with swivel	20	360, 341	140	-
822102500443	25	3,400,917	16 kN gate rated double action steel snap hook, with swivel	20	360, 341, 1496	140	+
822101500440	15	3,400,961	16 kN gate rated double action steel snap hook, with swivel	14,5	360, 341	140	-
822101500441	15	3,400,944	16 kN gate rated double action steel snap hook, with swivel	14,5	360, 341, 1496	140	+
822102500441	25	3,400,916	16 kN gate rated double action steel snap hook, with swivel	20	360, 341, 1496	140	+

Mennens Belgium
sales@mennensbelgium.be
+32 (0)3 253 23 23
© November 2026 - All Rights Reserved