MENNENS | Lifting Solutions Group
Axel Johnson International

Mobi Lok Vacuüm Anchor System

Product information



Vacuum anchor system. For use on flat or slightly bending surfaces: aviation, bulk tanks, etc.

- For use as a single anchor point, or as anchorages for a horizontal lifeline system.
- Mobi Lok allows for use in any orientation, provided the surface meets the concitions as specified by the manufacturer.
- Also for use in potentially explosive atmospheres - ATEX.

Max. number of users: 2, or 4, in a hll system with adaptations.

Safe temperature range:
Air: -29°C to 46°C
Surface: -29°C to 40°C

... *Read more*

Marking: According to standard
Standard: EN 795-B

Mennens Belgium
sales@mennensbelgium.be
+32 (0)3 253 23 23

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Mobi Lok Vacuüm Anchor System

Technical data

Part code	Max. number of persons	Description	Ref.	Max user weight kg
84152200126	2	Primary anchor unit for bottle air	2,200,126	136
84152200127	2	Secondary anchor pad	2,200,127	136
84152200125	2	Primary anchor unit for shop air	2,200,125	136

Mennens Belgium
sales@mennensbelgium.be
+32 (0)3 253 23 23

© November 2026 - All Rights Reserved