



Loop 35 kN Yellow Skylotec

Product information

The webbing slings in yellow made of polyamide can be used as a mobile anchor point. They have a diameter of 25mm and a load capacity of 35 kN and are mainly used in the construction industry.

Material: Polyamide

Marking: According to standard, CE-marked, Supplier symbol, product id, art no, serial no, production year, standards, max. load.

Temperature range: -35°C up to 45°C.

Standard: EN 354, EN 566, EN 795-B

Part code	Diameter mm	Min. breaking force kN	Max. number of persons	Length m	Colour	Weight kg
19.04L-0010-GE-0,4	25	35	1	0.4	Yellow	0.06
19.04L-0010-GE-0,6	25	35	1	0.6	Yellow	0.09
19.04L-0010-GE-0,8	25	35	1	0.8	Yellow	0.11
19.04L-0010-GE-1	25	35	1	1	Yellow	0.14
19.04L-0010-GE-1,2	25	35	1	1.2	Yellow	0.16
19.04L-0010-GE-1,5	25	35	1	1.5	Yellow	0.2
19.04L-0010-GE-1,8	25	35	1	1.8	Yellow	0.23
19.04L-0010-GE-2	25	35	1	2	Yellow	0.26
19.04L-0010-GE-4	25	35	1	4	Yellow	0.51