

STOBITEX Wear Protection Sleeve PU-1/single

Product information



Special wear protection for roundslings and webbing slings, intended for lift of load with cutting edges. Extremely good cutting resistance and high wear strength.

Also available as double sided sheathes, STOBITEX Wear Protection Sleeve PU-2/double side.

Material: Polyurethane.

Temperature range: Approx. -30° up to +70°C, short expose to approx. +90°C.

| Part code | Size | Inside width mm | Height mm | For 2 layer lifting mm | For 4 layer lifting mm | For roundslings ton | Weight kg/m |
|---------------|------|-----------------|-----------|------------------------|------------------------|---------------------|-------------|
| 12.4000200020 | 50 | 40 | 10 | 30 | - | - | 0.85 |
| 12.4000200030 | 50 | 40 | 20 | - | 30 | - | 0.9 |
| 12.4000200060 | 70 | 60 | 12 | 50 | - | - | 1.25 |
| 12.4000200061 | 70 | 60 | 17 | - | 50 | - | 1.3 |
| 12.4000200070 | 80 | 70 | 12 | 60 | - | - | 1.3 |
| 12.4000200090 | 80 | 70 | 24 | - | 60 | - | 1.35 |
| 12.4000200095 | 85 | 75 | 12 | - | - | 1 | 1.35 |
| 12.4000200110 | 95 | 85 | 24 | - | - | 2 | 1.5 |

| | | | | | | | |
|---------------|-----|-----|----|-----|-----|----|------|
| 12.4000200120 | 110 | 100 | 12 | 90 | - | - | 1.55 |
| 12.4000200130 | 110 | 100 | 17 | - | - | 3 | 1.6 |
| 12.4000200140 | 110 | 100 | 24 | - | 90 | - | 1.6 |
| 12.4000200190 | 145 | 135 | 12 | 120 | - | - | 2 |
| 12.4000200200 | 145 | 135 | 24 | - | 120 | - | 2.1 |
| 12.4000200240 | 170 | 160 | 12 | 150 | - | - | 2.3 |
| 12.4000200250 | 170 | 160 | 17 | - | - | 6 | 2.4 |
| 12.4000200260 | 170 | 160 | 24 | - | 150 | - | 2.4 |
| 12.4000200280 | 200 | 190 | 12 | 180 | - | - | 2.6 |
| 12.4000200290 | 200 | 190 | 17 | - | - | 8 | 2.65 |
| 12.4000200300 | 200 | 190 | 24 | - | 180 | - | 2.7 |
| 12.4000200320 | 230 | 220 | 36 | - | - | 10 | 3.5 |
| 12.4000200340 | 260 | 250 | 15 | 240 | - | - | 3.9 |
| 12.4000200360 | 290 | 280 | 30 | - | - | 15 | 4.4 |
| 12.4000200370 | 330 | 320 | 15 | 300 | - | - | 4.4 |
| 12.4000200380 | 330 | 320 | 30 | - | 300 | - | 4.8 |
| 12.4000200390 | 330 | 320 | 45 | - | - | 20 | 5.3 |

Blueprint

