

## STOBITEX Wear Protection Sleeve PU-1/single

---

### Product information

Special wear protection for roundslings and webbing slings, intended for lift of load with cutting edges. Extremely good cutting resistance and high wear strength.

Also available as double sided sheathes, STOBITEX Wear Protection Sleeve PU-2/double side.

... [Read more](#)



---


**Material:** Polyurethane.

**Temperature range:** Approx. -30° up to +70°C, short expose to approx. +90°C.

## STOBITEX Wear Protection Sleeve PU-1/single

---

Blueprint



## STOBITEX Wear Protection Sleeve PU-1/single

### Technical data

| Part code     | Size | Inside width mm | Height mm | For 2 layer lifting mm | For 4 layer lifting mm | For roundslings ton | Weight kg/m |
|---------------|------|-----------------|-----------|------------------------|------------------------|---------------------|-------------|
| 12.4000200020 | 50   | 40              | 10        | 30                     | -                      | -                   | 0.85        |
| 12.4000200030 | 50   | 40              | 20        | -                      | 30                     | -                   | 0.9         |
| 12.4000200060 | 70   | 60              | 12        | 50                     | -                      | -                   | 1.25        |
| 12.4000200061 | 70   | 60              | 17        | -                      | 50                     | -                   | 1.3         |
| 12.4000200070 | 80   | 70              | 12        | 60                     | -                      | -                   | 1.3         |
| 12.4000200090 | 80   | 70              | 24        | -                      | 60                     | -                   | 1.35        |
| 12.4000200095 | 85   | 75              | 12        | -                      | -                      | 1                   | 1.35        |
| 12.4000200110 | 95   | 85              | 24        | -                      | -                      | 2                   | 1.5         |
| 12.4000200120 | 110  | 100             | 12        | 90                     | -                      | -                   | 1.55        |
| 12.4000200130 | 110  | 100             | 17        | -                      | -                      | 3                   | 1.6         |
| 12.4000200140 | 110  | 100             | 24        | -                      | 90                     | -                   | 1.6         |
| 12.4000200190 | 145  | 135             | 12        | 120                    | -                      | -                   | 2           |
| 12.4000200200 | 145  | 135             | 24        | -                      | 120                    | -                   | 2.1         |
| 12.4000200240 | 170  | 160             | 12        | 150                    | -                      | -                   | 2.3         |
| 12.4000200250 | 170  | 160             | 17        | -                      | -                      | 6                   | 2.4         |
| 12.4000200260 | 170  | 160             | 24        | -                      | 150                    | -                   | 2.4         |
| 12.4000200280 | 200  | 190             | 12        | 180                    | -                      | -                   | 2.6         |
| 12.4000200290 | 200  | 190             | 17        | -                      | -                      | 8                   | 2.65        |
| 12.4000200300 | 200  | 190             | 24        | -                      | 180                    | -                   | 2.7         |
| 12.4000200320 | 230  | 220             | 36        | -                      | -                      | 10                  | 3.5         |
| 12.4000200340 | 260  | 250             | 15        | 240                    | -                      | -                   | 3.9         |
| 12.4000200360 | 290  | 280             | 30        | -                      | -                      | 15                  | 4.4         |
| 12.4000200370 | 330  | 320             | 15        | 300                    | -                      | -                   | 4.4         |
| 12.4000200380 | 330  | 320             | 30        | -                      | 300                    | -                   | 4.8         |
| 12.4000200390 | 330  | 320             | 45        | -                      | -                      | 20                  | 5.3         |