

STOBITEX Wear Protection Sleeve PU-2/double side

Product information



Special wear protection for roundslings and webbing slings, intended for lift of load with cutting edges. Extremely good cutting resistance and high wear strength.

Also available as single sided sheathes, STOBITEX Wear Protection Sleeve PU-1/single.


... [Read more](#)

Material: Polyurethane.

Temperature range: Approx. -30° - +70°C, short expose to apx +90°C.

STOBITEX Wear Protection Sleeve PU-2/double side

Blueprint



Technical data

| Part code | Code | For 2 layer lifting mm | For lashings | For 4 layer lifting mm | For webbing sling t | a mm | h mm | i mm | w mm | Weight kg |
|---------------|-------------------|---------------------------|--------------|---------------------------|------------------------|------|------|------|------|--------------|
| 12.4000201050 | PU-2 66/60/4/3 | - | 50 | - | - | 70 | 4 | 60 | 3 | 0.85 |
| 12.4000201020 | PU-2 50/40/10/5 | 30 | 35 | - | - | 50 | 10 | 40 | 5 | 1.1 |
| 12.4000201060 | PU-2 70/60/12/5 | 50 | - | - | - | 70 | 12 | 60 | 5 | 1.45 |
| 12.4000201070 | PU-2 80/70/12/5 | 60 | - | - | - | 80 | 12 | 70 | 5 | 1.6 |
| 12.4000201100 | PU-2 95/85/12/5 | 75 | 75 | - | - | 95 | 12 | 85 | 5 | 2 |
| 12.4000201120 | PU-2 110/100/12/5 | 90 | - | - | - | 110 | 12 | 100 | 5 | 2.1 |
| 12.4000201190 | PU-2 145/135/12/5 | 120 | - | - | - | 145 | 12 | 135 | 5 | 2.8 |
| 12.4000201240 | PU-2 170/160/12/5 | 150 | - | - | - | 170 | 12 | 160 | 5 | 3.4 |
| 12.4000201280 | PU-2 200/190/12/5 | 180 | - | - | - | 200 | 12 | 190 | 5 | 3.8 |
| 12.4000201370 | PU-2 330/320/15/8 | 300 | - | - | - | 330 | 15 | 320 | 8 | 7.2 |
| 12.4000201380 | PU-2 330/320/30/8 | - | - | 300 | - | 330 | 30 | 320 | 8 | 7.8 |
| 12.4000201390 | PU-2 330/320/45/8 | - | - | - | 20 | 330 | 45 | 320 | 8 | 8.4 |
| 12.4000201030 | PU-2 50/40/20/5 | - | - | 30 | - | 50 | 20 | 40 | 5 | - |
| 12.4000201065 | PU-2 70/60/17/5 | - | - | 50 | - | 70 | 17 | 60 | 5 | - |
| 12.4000201085 | PU-2 85/75/17/5 | - | - | - | 1 | 85 | 17 | 75 | 5 | - |
| 12.4000201090 | PU-2 80/70/24/5 | - | - | 60 | - | 80 | 24 | 70 | 5 | - |
| 12.4000201110 | PU-2 95/85/24/5 | - | - | 75 | 2 | 95 | 12 | 85 | 5 | - |
| 12.4000201130 | PU-2 110/100/17/5 | - | - | - | 3 | 110 | 17 | 100 | 5 | - |
| 12.4000201140 | PU-2 110/100/24/5 | - | - | 90 | - | 110 | 24 | 100 | 5 | - |
| 12.4000201200 | PU-2 145/135/24/5 | - | - | 120 | - | 145 | 24 | 135 | 5 | - |
| 12.4000201250 | PU-2 170/160/17/5 | - | - | - | 6 | 170 | 17 | 160 | 5 | - |
| 12.4000201260 | PU-2 170/160/24/5 | - | - | 150 | - | 170 | 24 | 160 | 5 | - |

STOBITEX Wear Protection Sleeve PU-2/double side

Technical data

| Part code | Code | For 2 layer lifting mm | For lashings | For 4 layer lifting mm | For webbing sling t | a mm | h mm | i mm | w mm mm | Weight kg |
|---------------|-------------------|---------------------------|--------------|---------------------------|------------------------|------|------|------|---------|--------------|
| 12.4000201290 | PU-2 200/190/17/5 | - | - | - | 8 | 200 | 17 | 190 | 5 | - |
| 12.4000201300 | PU-2 200/190/24/5 | - | - | 180 | - | 200 | 24 | 190 | 5 | - |
| 12.4000201320 | PU-2 230/220/36/5 | - | - | - | 10 | 230 | 36 | 220 | 5 | - |
| 12.4000201340 | PU-2 260/250/15/8 | 240 | - | - | - | 260 | 15 | 250 | 8 | - |
| 12.4000201360 | PU-2 290/280/30/8 | - | - | 240 | 15 | 290 | 30 | 280 | 8 | - |