



STOBIFORM Corner Protection KW

Product information

Corner protection made of polyurethane elastomer for protecting your textile lifting slings, your web lashing and / or for protection of the load when lifting or lashing on sharp edged loads such as steel coils. Usable with web lashing, webbing slings up to 300mm webbing width, wire rope slings up to \varnothing 40mm and chain slings up to \varnothing 20mm.

2 available standard types:

- type KW : Without magnets
- Type KWM: Equiped with magnets for easier fixation to the load

Recommended types for use with chain slings:

KW(M)25: \varnothing 6-8 mm

KW(M)45: \varnothing 8-10-13 mm

KW(M)65: \varnothing 13-16-18-19-20 mm

KW(M)75: \varnothing 19 - 20 mm

Other sizes and designs on request

Design with perforated metal bracket as an insert can also be supplied on request.

Material: Polyurethane-Elastomer.

Part code	Band width mm	Type	Number of Magnets	Weight kg
8025KW025	25	Stobiform KW25	0	0.6
8025KW040	40	Stobiform KW40	0	0.7
8025KW065	65	Stobiform KW65	0	0.8
8025KW075	75	Stobiform KW75	0	0.9
8025KW100	100	Stobiform KW100	0	1.1
8025KW125	125	Stobiform KW125	0	1.3
8025KW150	150	Stobiform KW150	0	1.5
8025KW200	200	Stobiform KW200	0	2.1
8025KW300	300	Stobiform KW300	0	2.8

Blueprint

