



## Master Link Assembly Pewag VSW 2-4

### Product information

This master link assembly is designed for the effortless creation of II- and IV-leg chain slings in the assembled or welded system. The flattened section on the transition links opens up additional, universal connection possibilities. Extra-large rings make this master link assembly the perfect partner for crane hooks according to DIN 15401 up to no. 40 and according to DIN 15402 up to no. 50.

**Material:** High-alloy quenched and tempered steel

**Marking:** According to standard, CE-marked, brand, grade

**Temperature range:** -40° up to +380°

**Standard:** EN 1677-4

**Safety factor:** 4:1

**Grade:** 10

| Part code | Code               | WLL ton | For chain, 2-leg mm | For chain, 3-4-leg mm | d mm | e mm | s mm | t mm | w mm | Weight kg |
|-----------|--------------------|---------|---------------------|-----------------------|------|------|------|------|------|-----------|
| 11.029314 | VSW 2-10 / 4-8     | 5.6     | 10                  | 8                     | 30   | 515  | 24   | 430  | 220  | 8.16      |
| 11.029315 | VSW 2-13 / 4-10    | 9.5     | 13                  | 10                    | 33   | 515  | 26   | 430  | 220  | 9.66      |
| 11.029317 | VSW 2-16 / 4-13    | 14      | 16                  | 13                    | 36   | 545  | 29   | 430  | 220  | 12.32     |
| 11.029319 | VSW 2-19/20 / 4-16 | 21.2    | 19/20               | 16                    | 45   | 570  | -    | 430  | 220  | 19.54     |

## Blueprint

