



## Master Link Assembly Pewag VSW 2-4

### Product information

This master link assembly is designed for the effortless creation of II- and IV-leg chain slings in the assembled or welded system. The flattened section on the transition links opens up additional, universal connection possibilities. Extra-large rings make this master link assembly the perfect partner for crane hooks according to DIN 15401 up to no. 40 and according to DIN 15402 up to no. 50.

**Material:** High-alloy quenched and tempered steel

**Marking:** According to standard, CE-marked, brand, grade

**Temperature range:** -40° up to +380°

**Standard:** EN 1677-4

**Safety factor:** 4:1

**Grade:** 10

| Part Code | Code               | WLL<br>ton | Chain 2 legs | Chain 3 and 4 legs | Single hook DIN 15401 no. | Double hook DIN 15402 no. | d<br>mm | e<br>mm | s<br>mm | t<br>mm | w<br>mm | Weight<br>kg |
|-----------|--------------------|------------|--------------|--------------------|---------------------------|---------------------------|---------|---------|---------|---------|---------|--------------|
| 11.029314 | VSW 2-10 / 4-8     | 5.6        | 10           | 8                  | 40                        | 50                        | 30      | 515     | 24      | 430     | 220     | 8.16         |
| 11.029315 | VSW 2-13 / 4-10    | 9.5        | 13           | 10                 | 40                        | 50                        | 33      | 515     | 26      | 430     | 220     | 9.66         |
| 11.029317 | VSW 2-16 / 4-13    | 14         | 16           | 13                 | 40                        | 50                        | 36      | 545     | 29      | 430     | 220     | 12.32        |
| 11.029319 | VSW 2-19/20 / 4-16 | 21.2       | 19/20        | 16                 | 40                        | 50                        | 45      | 570     | -       | 430     | 220     | 19.54        |

## Blueprint

