



## Pipe Lifting TBC - TBC-A

### Product information

Lightweight clamp with pressure resistant plastic cam for vertical concrete pipe lifting

#### Application

- For vertical lifting and transporting of concrete pipes and wells
- Terrier TBC / TBC-A lifting clamps must always be used in pairs (or per three clamps)
- TBC jaw opening available from: 60 to 120 mm
- TBC-A has an extra large jaw opening available from: 50 to 220 mm (adjustable in steps of 25 mm)
- Working load limit (WLL) 1000kg
- Other jaw openings available upon request

#### Features and benefits

- The cam is covered with a special high quality pressure resistant plastic
- Maintenance-friendly clamp, plastic pressure resistant cover is easy to change
- Tough quality welded body
- Lightweight design for easy handling

**Marking:** According to standard, CE-marked

**Temperature range:** -40°C up to 50°C

**Standard:** EN 13155

| Code    | WLL<br>ton | Beam width<br>mm | Jaw width<br>mm | S<br>mm | T<br>mm | U<br>mm | W<br>mm | X<br>mm | Y<br>mm | Z<br>mm |
|---------|------------|------------------|-----------------|---------|---------|---------|---------|---------|---------|---------|
| 1 TBC   | 1          | 60-120           | 60-120          | 169     | 12      | 326     | 97      | 60      | 12      | 40      |
| 1 TBC-A | 1          | 50-220           | 50-220          | 262     | 12      | 459     | 106     | 60      | 12      | 40      |

## Blueprint

