

Bow Shackle with Screw Collar Pin Yellow Pin G-3161

Product information



Bow shackles with screw pin.

Certification on request: 2.1, 2.2

Standard: Generally to US Fed. Spec. RR-C-271.

... [Read more](#)

Material: Bow and pin high tensile steel.

Marking: CE-marked

Finish: Hot dipped galvanized.


Note: Import quality

Safety factor: 6:1

Grade: 6

Bow Shackle with Screw Collar Pin Yellow Pin G-3161

Blueprint



Technical data

| Part code | Diameter mm | WLL ton | a mm | b mm | c mm | d mm | e mm | f mm | Weight kg |
|---------------|-------------|---------|------|------|------|------|------|------|-----------|
| 11.31LRYHBB05 | 14 | 0.33 | 5 | 6 | 14 | 9.5 | 22 | 15 | 0.03 |
| 11.31LRYHBB06 | 16 | 0.5 | 6 | 8 | 16 | 12 | 29 | 20 | 0.05 |
| 11.31LRYHBB08 | 19 | 0.75 | 8 | 10 | 19 | 13.5 | 31 | 21 | 0.08 |
| 11.31LRYHBB10 | 23 | 1 | 10 | 11 | 23 | 17 | 37 | 26 | 0.14 |
| 11.31LRYHBB11 | 27 | 1.5 | 11 | 13 | 27 | 19 | 43 | 29 | 0.2 |
| 11.31LRYHBB13 | 30 | 2 | 13 | 16 | 30 | 20 | 48 | 33 | 0.33 |
| 11.31LRYHBB16 | 38 | 3.25 | 16 | 19 | 38 | 27 | 60 | 43 | 0.62 |
| 11.31LRYHBB19 | 46 | 4.75 | 19 | 22 | 46 | 32 | 71 | 50 | 1.07 |
| 11.31LRYHBB22 | 53 | 6.5 | 22 | 25 | 53 | 36 | 84 | 58 | 1.62 |
| 11.31LRYHBB25 | 61 | 8.5 | 25 | 28 | 61 | 43 | 95 | 68 | 2.28 |
| 11.31LRYHBB28 | 68 | 9.5 | 28 | 32 | 68 | 46 | 108 | 74 | 3.36 |
| 11.31LRYHBB32 | 76 | 12 | 32 | 35 | 76 | 51 | 119 | 82 | 4.31 |
| 11.31LRYHBB35 | 84 | 13.5 | 35 | 38 | 84 | 57 | 133 | 92 | 6.14 |
| 11.31LRYHBB38 | 92 | 17 | 38 | 42 | 92 | 60 | 146 | 98 | 7.81 |
| 11.31LRYHBB45 | 106 | 25 | 45 | 50 | 106 | 73 | 177 | 127 | 12.61 |