

Dee Shackle with Screw Pin Green Pin® MDVI, Stainless Steel

Product information



The Green Pin® Stainless Steel Dee Shackle is a grade 5 dee shackle with a screw collar pin. The screw pin enables quick (dis)assembly which makes the shackle perfect for rigging activities in which assembly and disassembly occur relatively frequently. The Green Pin® Stainless Steel Dee Shackle can be used for both one-leg and multi-leg systems. The shackle is available in a range with a working load limit from 0.4 up to 6 ton.

Certification on request: 2.1, 2.2, 3.1

[... Read more](#)

Material: AISI 316

Marking: CE-marked

Temperature range: -40°C up to +200°C

Finish: Polished.


Note: WLL

Safety factor: 5:1

Grade: 5

Dee Shackle with Screw Pin Green Pin® MDVI, Stainless Steel

Blueprint



Technical data

| Code | WLL ton | Size | a mm | b mm | c mm | d mm | e mm | f mm | Weight kg |
|---------|---------|------|------|------|------|------|------|------|-----------|
| MDV0.4I | 0.4 | 52 | 8 | 8 | 16 | 16 | 32 | 52 | 0.06 |
| MDV0.6I | 0.6 | 64 | 10 | 10 | 19 | 20 | 40 | 64 | 0.11 |
| MDV0.9I | 0.9 | 78 | 12 | 12 | 24 | 25 | 48 | 78 | 0.19 |
| MDV1.5I | 1.5 | 90 | 13 | 16 | 31 | 24 | 52 | 90 | 0.3 |
| MDV2.5I | 2.5 | 110 | 16 | 20 | 38 | 28 | 64 | 110 | 0.57 |
| MDV3I | 3 | 124 | 19 | 22 | 44 | 32 | 72 | 124 | 0.9 |
| MDV4I | 4 | 134 | 22 | 25 | 50 | 37 | 74 | 134 | 1.33 |
| MDV6I | 6 | 162 | 25 | 30 | 57 | 40 | 94 | 162 | 1.98 |