

Dee Shackle SC Green Pin® Pin G-4151

Product information



The Green Pin® Dee Shackle SC is a dee shackle with a screw collar pin. The screw pin enables quick (dis)assembly which makes the shackle perfect for rigging activities in which assembly and disassembly occur relatively frequently. Due to the galvanization of the shackle its long-term durability is assured. Furthermore, the shackle's design reduces the wear of (wire) rope as the screw thread is hidden in a chamber. Particularly important for use offshore, the Green Pin® Dee Shackle SC conforms to a wide range of certifications from class societies such as DNV GL. The Green Pin® Dee Shackle SC is suitable for one-leg lifting systems only and is available in a range with a working load limit from 0.33 up to 55 ton.

Certification on request: 2.1, 2.2, 3.1, MTCa, DNVGL-ST-0378, ABS PDA ARS MA
... [Read more](#)

Material: Bow and pin high tensile steel, quenched and tempered

Marking: According to standard, CE-marked

Temperature range: -40°C up to +200°C

Finish: Hot dip galvanized


Standard: EN 13889

Safety factor: 6:1

Grade: 6

Dee Shackle SC Green Pin® Pin G-4151

Blueprint



Technical data

Part code	WLL ton	A mm	B mm	C mm	D mm	e mm mm	f mm mm	g mm mm	h mm mm	Weight kg
11.30PGDDB05	0.33	5	6	12	5	9,5	19	33	29,5	0.02
11.30PGDDB06	0.5	7	8	16,5	7	12	22	41,5	38	0.05
11.30PGDDB08	0.75	9	10	20	9	13,5	26	50	46,5	0.09
11.30PGDDB10	1	10	11	22,5	10	17	32	59	54	0.14
11.30PGDDB11	1.5	11	13	26,5	11	19	37	68	59,5	0.19
11.30PGDDB13	2	13,5	16	34	13	22	43	81	73	0.32
11.30PGDDB16	3.25	16	19	40	16	27	51	97	89	0.54
11.30PGDDB19	4.75	19	22	46	19	31	59	112	103	0.87
11.30PGDDB22	6.5	22	25	52	22	36	73	134	119	1.34
11.30PGDDB25	8.5	25	28	59	25	43	85	154	137	2.08
11.30PGDDB28	9.5	28	32	66	28	47	90	167	153	2.77
11.30PGDDB32	12	32	35	72	32	51	94	180	170	3.72
11.30PGDDB35	13.5	35	38	80	35	57	115	209	186	5.14
11.30PGDDB38	17	38	42	88	38	60	127	230	203	6.85
11.30PGDDB45	25	45	50	103	45	74	149	271	243	11.45
11.30PGDDB50	35	50	57	111	50	83	171	305	272	16.86
11.30PGDDB57	42.5	57	65	130	57	95	190	345	310	24.61
11.30PGDDB65	55	65	70	145	65	105	203	376	344	32.65