MENNENS | Lifting Solutions Group
Axel Johnson International

Turnbuckle BN Jaw - Jaw Green Pin® G-6323

Product information



The Green Pin® JJ Turnbuckle BN is a turnbuckle with jaw-jaw end-fitting and a safety bolt, generally to ASTM F1145-92. One of the unique features of Green Pin® Turnbuckles such as this one is that they can be used for both lifting and lashing. The turnbuckle also offers a double safety (cotter pin and safety bolt) which prevents accidental unscrewing of the pin. The Green Pin® JJ Turnbuckle BN is available in a range with a diameter thread of 3/8" (take up of 6") up to 2 3/4" (take up of 24").

Certification on request: 2.1, 2.2, 3.1, MTCa

Standard: Generally to ASTM F1145-92 formerly U.S. Federal Specification FF-T-791b.

... *Read more*

Material: Drop forged high tensile steel SAE 1035 or 1045
Marking: CE-mark
Temperature range: -20°C up to +200°C
Finish: Hot dipped galvanized

Safety factor: 5:1


Mennens Belgium
sales@mennensbelgium.be
+32 (0)3 253 23 23

© November 2026 - All Rights Reserved

MENNENS | Lifting Solutions Group
Axel Johnson International

Turnbuckle BN Jaw - Jaw Green Pin® G-6323

Blueprint



Technical data

Part code	WLL ton	Thread Inch	Take up inch	a " mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	Weight kg
422100050300	0.54	3/8	6	3/8	273	409	304	12	21	7	9	21	0.55
422100100300	1	1/2	6	1/2	304	435	343	16	26	10	11	25	0.96
422100100305	1	1/2	9	1/2	379	588	418	16	26	10	11	25	1.18
422100100306	1	1/2	12	1/2	455	740	494	16	26	10	11	25	1.5
422100160300	1.59	5/8	6	5/8	346	469	406	18	32	13	14	33	1.75
422100160305	1.59	5/8	9	5/8	421	622	480	18	32	13	14	33	2.14
422100160306	1.59	5/8	12	5/8	498	774	557	18	32	13	14	33	2.43
422100240300	2.36	3/4	6	3/4	369	487	439	24	38	16	16	41	2.7
422100240305	2.36	3/4	9	3/4	444	640	514	24	38	16	16	41	3.23
422100240306	2.36	3/4	12	3/4	520	792	590	24	38	16	16	41	3.57
422100240307	2.36	3/4	18	3/4	670	1,096	740	24	38	16	16	41	4.55
422100330300	3.27	7/8	12	7/8	561	826	638	27	42	19	19	48	5.22
422100330305	3.27	7/8	18	7/8	713	1,132	790	27	42	19	19	48	6.56
422100450305	4.54	1	6	1	447	554	532	31	50	22	20	54	5.54
422100450306	4.54	1	12	1	598	859	683	31	50	22	20	54	6.96
422100450307	4.54	1	18	1	750	1,168	835	31	50	22	20	54	8.4
422100450300	4.54	1	24	1	903	1,470	988	31	50	22	20	54	8.9
422100690300	6.9	1 1/4	12	1 1/4	643	916	748	44	71	28	26	68	11.9
422100690305	6.9	1 1/4	18	1 1/4	805	1,230	910	44	71	28	26	68	13.6
422100690306	6.9	1 1/4	24	1 1/4	964	1,541	1,069	44	71	28	26	68	14.2
422100970300	9.71	1 1/2	12	1 1/2	675	942	806	52	71	35	28	80	18.5
422100970305	9.71	1 1/2	18	1 1/2	825	1,244	956	52	71	35	28	80	19.3

Mennens Belgium
sales@mennensbelgium.be
+32 (0)3 253 23 23

© November 2026 - All Rights Reserved

MENNENS | Lifting Solutions Group
Axel Johnson International

Turnbuckle BN Jaw - Jaw Green Pin® G-6323

Technical data

Part code	WLL ton	Thread Inch	Take up inch	a " mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	Weight kg
422100970306	9.71	1 1/2	24	1 1/2	980	1,551	1,111	52	71	35	28	80	22
422101270300	12.7	1 3/4	18	1 3/4	938	1,316	1,092	60	86	41	33	90	30
422101270305	12.7	1 3/4	24	1 3/4	1,089	1,621	1,243	60	86	41	33	90	33
422101680300	16.8	2	24	2	1,153	1,673	1,338	63	93	50	40	107	50
422102720300	27.2	2 1/2	24	2 1/2	1,255	1,831	1,480	75	114	57	41	143	92
422103400300	34	2 3/4	24	2 3/4	1,348	1,882	1,604	90	110	70	41	158	109

Mennens Belgium
sales@mennensbelgium.be
+32 (0)3 253 23 23

© November 2026 - All Rights Reserved