MENNENS | Lifting Solutions Group
Axel Johnson International

Trec LH Mobile shelf ladder

Product information



General: For easy rolling along the shelves: The solution is equipped with guide rails and self-locking sprung castors and can be customised to the desired height. In case of order, please provide the distance from the floor to the top edge of the rail.

Features and benefits:
- Both the top of the ladder and the self-locking sprung castors at the bottom lock the shelf ladder when weight is applied.
- When not in use, the ladder can be stowed vertically on the shelf to save space.

Available in 3 Types:

1. **Comfortstep Trec LH** (ladder width 380 mm)
   Screwed tread with padded front edge.
   Base length = vertical height of the guide rail × 0.404
2. **Saferstep Trec LH** (ladder width 420 mm)
   Edge-formed tread with ZARGES Safer Step Technology.
   Base length = vertical height of the guide rail × 0.364
3. **Stella Trec LH** (ladder width 490 mm)
   edge-formed wide rung.
   Base length = vertical height of the guide rail × 0.268

Accessoiries Optional (to be ordered separately):
A1: 99.XX40370 Aluminium alloy tube, ∅ 30 mm, 3000 mm long, anodised
A2: 99.XX41457 Aluminium alloy intermediate bracket.
A3: 99.XX41457 Aluminium alloy bracket with stop on the right
A4: 99.XX41457 Aluminium alloy bracket with stop on the left.
Rail systems: One intermediate bracket is required for every approx. 1.00 m of tubing.

... Read more

Material: Aluminium
Marking: According to standard
Finish: anodised
Standard: EN 131 Cat. Professional
Note: Max. load 150 kg.


Mennens Belgium
sales@mennensbelgium.be
+32 (0)3 253 23 23

© November 2026 - All Rights Reserved

MENNENS | Lifting Solutions Group
Axel Johnson International

Trec LH Mobile shelf ladder

Blueprint



Technical data

Part code	Type	number of treads	from/to maximum vertical hook-on height m	no. of rungs
909841412	1: Comfortstep Trec LH	6	1.84–2.08	-
909841413	1: Comfortstep Trec LH	7	2.09–2.33	-
909841414	1: Comfortstep Trec LH	8	2.34–2.58	-
909841415	1: Comfortstep Trec LH	9	2.59–2.83	-
909841416	1: Comfortstep Trec LH	10	2.84–3.08	-
90981141356	2: Saferstep Trec LH	6	1.67–2.16	-
90981141358	2: Saferstep Trec LH	8	2.17–2.67	-
90981141360	2: Saferstep Trec LH	10	2.68–3.20	-
90981141362	2: Saferstep Trec LH	12	3.21–3.72	-
90981141364	2: Saferstep Trec LH	14	3.73–4.25	-
90981141511	3: Stella Trec LH	-	1.73-2.26	6
90981141512	3: Stella Trec LH	-	2.27-2.80	8
90981141513	3: Stella Trec LH	-	2.81-3.34	10
90981141514	3: Stella Trec LH	-	3.35-3.88	12
90981141515	3: Stella Trec LH	-	3.89-4.42	14
909840370	A1	-	-	-
909841457	A2	-	-	-
909841458	A3 mm	-	-	-
909841459	A4 mm	-	-	-

Mennens Belgium
sales@mennensbelgium.be
+32 (0)3 253 23 23

© November 2026 - All Rights Reserved