

## Skyline 2E Rope-operated ladder, 2-part

---

### Product information



**General:** Easy and convenient vertical height adjustment makes this ladder ideal for use to access very great heights.

#### Features and benefits:

- A high level of stability thanks to extra-wide bottom ladder (490 mm).
- Very easy and convenient rung-by-rung height adjustment in a 280 mm grid via synthetic rope and roller.
- Locks securely thanks to automatic spring loaded pawls.
- Top ladder section fitted with wall wheels.
- Wheel assemblies with abrasion-resistant surfaces that will not damage the wall.
- High strength, non-twist rung/stile connections.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.

... [Read more](#)

---

**Material:** Aluminium

**Marking:** According to standard

**Finish:** Natural

**Standard:** EN 131 Cat. Professional

**Note:** Max. load 150 kg.

## Skyline 2E Rope-operated ladder, 2-part

### Technical data

Part code	working height approx. m	stile height mm	number of rungs	ladder length, extended m	ladder length, retracted m	Width horizontal stabiliser bar m	Weight kg
99.XX40206	7.9	73	2 × 14	7.21	4.14	1.2	22.8
99.XX40207	9	98	2 × 16	8.33	4.7	1.2	24.7
99.XX40208	9.75	98	2 × 18	9.13	5.2	1.2	30.9
99.XX40209	10.85	114	2 × 20	10.25	5.74	1.2	33.8
99.XX40212	11.7	114	2 × 22	11.1	6.4	1.2	37.9
99.XX40210	12.75	114	2 × 24	12.22	6.9	1.2	42.6