



Multi-function ladder Skymaster X, 3-part

Product information

General: Convertible to take on challenging tasks with greater safety. Offers high functionality and flexibility and an excellent price/performance ratio.

Features and benefits:

- Can be used on steps/stairs (code. 41536-41540 up to 3x10 rungs).
- One rigid locking bar.
- Upper ladder can also be used separately as single ladders for code. 41536-41540 up to 3x10 rungs.
- High-strength Perlon straps with sewn-in fixing tab to prevent splaying.
- Optimum wrap-around stile guide that encompasses the whole rung.
- Rung hook and stile guides are bolted in and can therefore be replaced.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping.
- Rungs and stiles made from aluminium extrusions.

Material: Aluminium

Marking: According to standard

Standard: EN 131 Cat. Professional

Note: Max load 150 kg.

Part code	stile height mm	ladder length, retracted m	ladder length as 3-part ladder m	single length as 2-part single ladder and as stepladder with push-on part m	max. working height as 3-part single ladder approx. m	Horizontal stabiliser bar m	no. of rungs	Weight kg
41536	68	1.9	4.1	3	5	0.8	3 x 6	13.8
41537	68	2.2	5	3.6	5.8	0.9	3 x 7	15
41538	73	2.45	5.8	4.1	6.65	1	3 x 8	17.5
41539	85	2.7	6.7	4.7	7.45	1.1	3 x 9	20
41540	85	3	6.9	4.95	7.7	1.1	3 x 10	23.3
41542	98	3.55	8.6	6.1	9.35	1.2	3 x 12	28.8
41544	98	4.15	9.7	6.95	10.4	1.2	3 x 14	36.4

Blueprint