



CREAXESS Mobile access steps with platform, Auto- or Ergo Stop

Product information

Mobile access or work platforms with easy-going steps. Ideal for work over long periods, even with tools and frequent changes of working position. Large-area platform with guardrail for safe and ergonomic working at heights.

Features and benefits:

- Different angles of inclination: 45° for comfortable access, 60° for confined spaces.
- Selection of tread widths 600 mm, 800 mm or 1000 mm.
- Serrated aluminium (R10) step and platform surfaces as standard. Steel gratings (R12) and perforated steel plates (R13) are also available for higher non-slip performance.
- Individually adjustable platform lengths.
- Platform steps instantly ready for use due to an innovative brake system.
- An antistatic version of the chassis is also available.
- ZARGES Ergo Stop - all four castors can be braked conveniently using the foot pedal on the flight of steps.
- Customised guardrail configuration on the platform, with optional swing door or pole barrier.
- Maximum flexibility with optional handrails and guardrails which can be removed without tools.
- Quick and simple assembly with the ZARGES connection system with a high level of pre-assembly.

We recommend equipping the product in accordance with the German Equipment and Product Safety Act (ProdSG) with two-sided handrails and, for steps with platforms or maintenance platforms, all-round fall protection (e.g. guardrails). If handrails or guardrails are not desired, the operator must ensure sufficient regulatory protection.

- Standard applied: DIN EN ISO 14 122.

I'd like to have more information about this service

CREAXESS Ergo Stop - Plattformtrap / Mobile access step / Échelle plate-forme mobile

Technical data

| access steps with platform, mobile, with double-sided handrail and peripheral platform railing - 45° inclination. | | | | | | | |
|---|--------------|------------------|---------------|--------------------------------------|-------|---------------------------------------|------|
| Vertical height | overall span | number of treads | chassis width | ZARGES auto stop* tread width 800 mm | | ZARGES ergo stop** tread width 800 mm | |
| mm | mm | | mm | order no. | | order no. | |
| 1070 | 2220 | 5 | 1000 | 402 | 59611 | 402 | 5965 |
| 1500 | 2650 | 7 | 1000 | 402 | 59613 | 402 | 5965 |
| 1930 | 3080 | 9 | 1000 | 402 | 59615 | 402 | 5965 |
| 2360 | 3510 | 11 | 1200 | 402 | 59617 | 402 | 5965 |
| 2790 | 3940 | 13 | 1400 | 402 | 59619 | 402 | 5965 |
| 3220 | 4370 | 15 | 1400 | 402 | 59621 | 402 | 5966 |
| 3650 | 4800 | 17 | 1400 | 402 | 59623 | 402 | 5966 |

| access steps with platform, mobile, with double sided handrail and peripheral platform railing - 60° inclination. | | | | | | | |
|---|--------------|------------------|---------------|--------------------------------------|-------|--|------|
| Vertical height | overall span | number of treads | chassis width | ZARGES auto stop* tread width 800 mm | | ZARGES ergo stop ** tread width 800 mm | |
| mm | mm | | mm | order no. | | order no. | |
| 1250 | 1942 | 5 | 1200 | 402 | 59631 | 402 | 5967 |
| 1750 | 2231 | 7 | 1200 | 402 | 59633 | 402 | 5967 |
| 2250 | 2519 | 9 | 1200 | 402 | 59635 | 402 | 5967 |
| 2750 | 2808 | 11 | 1400 | 402 | 59637 | 402 | 5967 |
| 3250 | 3097 | 13 | 1600 | 402 | 59639 | 402 | 5967 |
| 3750 | 3385 | 15 | 1600 | 402 | 59641 | 402 | 5968 |

