

Elevator rope 8x19S-FC

Product information



General: Steel wire rope for use in elevator.

Tolerance: ≤10 mm 0% - +6%, 10 mm 0% - +5%.

Rope construction: 8x19S-FC, Seal.


Marking: According to standard

Finish: Ungalvanised.

Standard: EN 12385-5

Fill factor: 0.44

Elevator



Part code	Rope diameter mm	Tensile strength N/mm ²	Finish	Rope lay	Min. breaking force kN	Steel area mm ²	Lubrication	Weight kg/100m
01.B10152080M	8	1,370/1,770	Bright	sZ	28.1	22	SupplierStandard	22.2
01.B10152090M	9	1,370/1,770	Bright	sZ	35.6	28.3	SupplierStandard	28
01.B10152100M	10	1,370/1,770	Bright	sZ	44	34.9	SupplierStandard	34
01.B10152110M	11	1,370/1,770	Bright	sZ	53.2	42.2	SupplierStandard	41
01.B10152120M	12	1,370/1,770	Bright	sZ	63.3	50.3	SupplierStandard	49
01.B10152130M	13	1,370/1,770	Bright	sZ	74.3	59	SupplierStandard	58
01.B10152140M	14	1,370/1,770	Bright	sZ	86.1	68.4	SupplierStandard	67
01.B10152160M	16	1,370/1,770	Bright	sZ	113	89.3	SupplierStandard	87