



Standard swivelling vacuum units 90°

Product information



Transported materials can be pivoted through 90° with these units.

When handling sheet metal, it is not always possible to transport the sheets horizontally. For instance, to feed a vertical saw or remove upright panels standing in a warehouse, it is necessary to have a swivelling range of 90°.

With vacuum lifters from AERO-LIFT swivelling is an easy and comfortable task even for a single worker when it comes to large and/ or heavy loads.

Functionality

Swivelling manually for loads up to 150 kg.

With a handle the load can be swivelled manually.

Comfortable swivelling with a lifting cylinder

Easy to operate with push buttons at the handle. Swivelling continuously without manpower of the user.

Description	Carrying capacity kg	Main traverse mm	Cross traverse mm	Suction plate quantity / Ø mm
AERO 125/4R-90°	125	1,800	1,000	4 / 170
AERO 125/4R-90°	125	2,200	1,000	4 / 170
AERO 125/4R-90°	125	3,000	1,000	4 / 170
AERO 125/8R-90°	125	1,800	1,000	8 / 120
AERO 125/8R-90°	125	2,200	1,000	8 / 120

AERO 125/8R-90°	125	3,000	1,000	8 / 120
AERO 125/12R-90°	125	3,000	1,000	12 / 110
AERO 250/4R-90°	250	1,800	1,000	4 / 250
AERO 250/4R-90°	250	2,200	1,000	4 / 250
AERO 250/4R-90°	250	3,000	1,000	4 / 250
AERO 250/8R-90°	250	1,800	1,000	8 / 170
AERO 250/8R-90°	250	2,200	1,000	8 / 170
AERO 250/8R-90°	250	3,000	1,000	8 / 170
AERO 250/12R-90°	250	3,000	1,000	12 / 160
AERO 500/4R-90°	500	1,800	1,000	4 / 350
AERO 500/4R-90°	500	2,200	1,000	4 / 350
AERO 500/4R-90°	500	3,000	1,000	4 / 350
AERO 500/8R-90°	500	1,800	1,000	8 / 250
AERO 500/8R-90°	500	2,200	1,000	8 / 250
AERO 500/8R-90°	500	3,000	1,000	8 / 250
AERO 500/12R-90°	500	3,000	1,000	12 / 210
AERO 1000/8R-90°	1,000	1,800	1,000	8 / 350
AERO 1000/8R-90°	1,000	2,200	1,000	8 / 350
AERO 1000/8R-90°	1,000	3,000	1,000	8 / 350
AERO 1000/12R-90°	1,000	3,000	1,000	12 / 270