MENNENS | Lifting Solutions Group
Axel Johnson International

Polypropylene Fibre Rope 3-Strand

Product information



General purpose rope for a variety of marine applications; mooring, towing, fishing, pick-up lines, lifting slings, general purpose use. Resistant to rot, most acids and alkalies. The fibre is UV-stabilized against sunlight.

Standard length: 220m : 4-16mm spool - 18-48mm coil
Specific gravity: 0,91 (floats).
Melting point: Approx. 165°C.
Elongation: Approx. 30%.
Strength wet/dry: 100%.
Shock absorption: Very good.
Water absorption: None.
Abrasion resistance: Good.

... *Read more*

Features: Spliced fibre.
Material: Polypropylene.
Marking: According to standard
Finish: Orange. Other colours possible on request.
Standard: EN ISO 1346

Mennens Belgium
sales@mennensbelgium.be
+32 (0)3 253 23 23

© November 2026 - All Rights Reserved

MENNENS | Lifting Solutions Group
Axel Johnson International

Polypropylene Fibre Rope 3-Strand

Technical data

Part code	Diameter mm	Length m	MBL kN	Rope ends	Weight kg/220m
300300402200130	4	220	2.7	Plain ends	1.6
300300502200130	5	220	3.9	Plain ends	2.4
300300602200130	6	220	5.4	Plain ends	3.7
300300802200130	8	220	9.4	Plain ends	6.6
300301002200130	10	220	14	Plain ends	10
300301202200130	12	220	19.9	Plain ends	14.5
300301402200130	14	220	27.4	Plain ends	20
300301602200130	16	220	34.3	Plain ends	25.5
300301802200130	18	220	43.6	Plain ends	32.5
300302002200130	20	220	52.7	Plain ends	39.5
300302202200130	22	220	63.7	Plain ends	48.5
300302402200130	24	220	74.5	Plain ends	57
300302602200130	26	220	87.8	Plain ends	67
300302802200130	28	220	99.1	Plain ends	78
300303202200130	32	220	126	Plain ends	101
300303602200130	36	220	158	Plain ends	129
300304002200130	40	220	190	Plain ends	158
300304402200130	44	220	229	Plain ends	194
300304802200130	48	220	266	Plain ends	229

Mennens Belgium
sales@mennensbelgium.be
+32 (0)3 253 23 23

© November 2026 - All Rights Reserved