MENNENS | Lifting Solutions Group
Axel Johnson International

# Hand spurgear Winch SS TIREX

**Product information**



Hand spurgear winch in compact design available in 150 and 300 kg, stainless steel model (with stainless steel mounting plate).

Suitable for moderate use both indoor and outdoor.

**Applications:**

- Lifting of doors
- Opening of hatches
- Moving a boat
- Scenery handling
- Lifting equipment

**Technical properties:**

- Chassis made of an aluminum frame.
- Composite drum.
- Planetary reducer
- Mounting plate in galvanised steel (standard model) or in 316L anti-corrosion stainless steel (stainless steel model).
- Flat mounted.
- 4 fixation points.
- Removable crank.
- Free spooling drum, only when not in load.
- Automatic brake in composite material.
- Failsafe system for correct rope winding direction (patented).

**Options:** Stainless steel Wire rope and hook or Fibre rope and Stainlessteel hook
... *Read more*

**Material:** Stainless steel
**Marking:** According to standard, CE-mark
**Temperature range:** -10°C to +50°C
**Standard:** EN 13157


**Mennens Belgium**
sales@mennensbelgium.be
+32 (0)3 253 23 23

© November 2026 - All Rights Reserved

MENNENS | Lifting Solutions Group
Axel Johnson International

# Hand spurgear Winch SS TIREX

## Blueprint



## Technical data

| Part code | WLL ton | Model | Rope Ø mm | WLL top layer ton | Number of layers | Lift per crank revolution mm | Hand force max. kg | Max. drum capacity m | Weight kg |
|---|---|---|---|---|---|---|---|---|---|
| 501300030000450 | 0.25 | TIREX150INOX | 4 | 0.15 | 6 | 40 | 8 | 24 | 3.7 |
| 501300040000450 | 0.4 | TIREX300INOX | 5 | 0.3 | 3 | 41 | 14 | 8.5 | 3.7 |

**Mennens Belgium**
sales@mennensbelgium.be
+32 (0)3 253 23 23

© November 2026 - All Rights Reserved