MENNENS | Lifting Solutions Group
Axel Johnson International

Roundsling Assembly RR-176

Product information



Design: Roundsling covered with extra protection sleeve and provided with strengthen eye in each end, assembled as tool in combination with lifting details in grade 8. Max manufacturing length 20 m.

Stretch with working load: 2-3%.

Length tolerance: Nominal length ±2%.

Safety factor: Forge 4:1 and round sling 7:1.

... *Read more*

Material: Polyester. Resistant to most acids but not strong alkalizes.
Marking: According to standard, The slings are provided with a label with manufacturer's symbol, working load limit (WLL) and CE marking.
Temperature range: app. -40° - +100°C.
Standard: EN 1492-2

Grade: 10

Mennens Belgium
sales@mennensbelgium.be
+32 (0)3 253 23 23

© November 2026 - All Rights Reserved

MENNENS | Lifting Solutions Group
Axel Johnson International

Roundsling Assembly RR-176

Technical data

Part code	WLL ton	Colour
RR17601	1	Violet
RR17602	2	Green
RR17603	3	Yellow
RR17604	4	Grey
RR17605	5	Red
RR17606	6	Brown
RR17608	8	Blue
RR17610	10	Orange

Mennens Belgium
sales@mennensbelgium.be
+32 (0)3 253 23 23

© November 2026 - All Rights Reserved