



Fall Arrest Block IKAR HWPB with Webbing

Product information

Robust, low-maintenance fall arrest device with webbing and swivel. The swivel prevents the webbing from twisting. Internal energy-absorber and hook with fall indicator.

Low weight thanks to extra light plastic housing.

Approved for vertical and horizontal use.

Edge tested: Tested at sharp edges, $R \geq 0,5$ mm (CNB/P/11.060 2008 sharp edge Type A)

Carabiner: IKAR Small swivel snap hook IKV11 ($L_k = 136,5$ mm -opening \varnothing 25 mm).

The blocks can also be delivered with the following approvals: ANSI/ASSE Z 359.14-2014/LE up on request.

Material: Body: plastic, webbing: Dyneema®

Marking: According to standard, CE-marked

Temperature range: -40°C to +50°C.

Standard: EN 360

| Part code | Code | Max. number of persons | Length m | Max load kg | Dimensions mm | L mm | B mm | T mm | Lk | Lk | Lk | Weight kg |
|-----------------|----------|------------------------|----------|-------------|----------------|------|------|------|-------|-------|-------|-----------|
| 19.0741-HWPB3,5 | HWPB 3.5 | 1 | 3.5 | 136 | 326 x 104 x 78 | 326 | 104 | 78 | - | 136.5 | - | 1.2 |
| 19.0741-HWPB5,5 | HWPB 5.5 | 1 | 5.5 | 136 | 300 x 130 x 78 | 300 | 130 | 78 | - | - | 136.5 | 1.5 |
| 19.0741-HWPB7 | HWPB 7 | 1 | 7 | 136 | 300 x 165 x 80 | 300 | 165 | 80 | - | - | 136.5 | 1.8 |
| 19.0741-HWPB9 | HWPB 9 | 1 | 9 | 136 | 335 x 168 x 88 | 355 | 168 | 88 | - | - | 136.5 | 2.3 |
| 19.0741-HWPB12 | HWPB 12 | 1 | 12 | 136 | 370 x 195 x 95 | 370 | 195 | 95 | 136.5 | - | - | 3.4 |
| 19.0741-HWPB15 | HWPB 15 | 1 | 15 | 136 | 400 x 195 x 95 | 400 | 195 | 95 | - | 136.5 | - | 4.8 |

Blueprint

