



Fall Arrest Block IKAR HWS with Galvanized Wire

Product information

Robust, low-maintenance fall arrest device with galvanized wire and swivel. The swivel prevents the wire from twisting. Internal energy-absorber and hook with fall indicator.

Low weight and maintenance thanks to extra light aluminium housing.

Approved for vertical and horizontal use.

Edge tested: Tested at sharp edges, $R \geq 0,5$ mm (CNB/P/11.060 2008 sharp edge Type A)

Carabiner: IKAR IKV21 (Lk = 186mm) small swivel snap hook (opening \varnothing 26 mm)

Can be delivered with other carabiners or scaffolding hooks up on request.

The blocks can be delivered with the following approvals: ANSI/ASSE Z 359.14-2014/LE up on request.

Material: Body: Aluminium

Marking: According to standard, CE-marked

Temperature range: -40°C up to +50°C.

Finish: Blue painted

Standard: EN 360

Part code	Code	Max. number of persons	Length m	Max load kg	L	B mm	T mm	Weight kg
19.0741-HWS6	41-HWS 6	1	6	136	400	145	80	3
19.0741-HWS9	41-HWS 9	1	9	136	455	160	85	3.7
19.0741-HWS12	41-HWS 12	1	12	136	490	190	95	5.4
19.0741-HWS18	41-HWS 18	1	18	136	540	220	97	6.9
19.0741-HWS24	41-HWS 24	1	24	136	575	250	97	8.4

Blueprint

