



Wire Rope Lifting Sling WLS-101

Product information

Standard steel wire rope construction: 6x36WS IWRC, 1960N/mm²*

(*ø 3mm - ø 7mm rope construction: 6x19M WSC 1960 N/mm²)

Design: Both ends mechanically spliced soft eyes

Load table at Technical Data -> Show table

Please specify the needed (working) length and eye diam/length with your request.

Other rope construction and/or end-terminations such as master links, shackles, hooks, etc.. possible on request. In that case, please check our website for more standard wire rope slings. You can also contact us to discuss the possible options or specify it with your request.

Part code	Diameter mm	WLL ton
WLS10103	3	0.12
WLS10104	4	0.21
WLS10105	5	0.32
WLS10106	6	0.47
WLS10108	8	0.82
WLS10109	9	1.04
WLS10110	10	1.28
WLS10111	11	1.55

WLS10112	12	1.84
WLS10113	13	2.17
WLS10114	14	2.51
WLS10116	16	3.3
WLS10118	18	4.1
WLS10120	20	5.1
WLS10122	22	6.2
WLS10124	24	7.38
WLS10126	26	8.66
WLS10128	28	10.04
WLS10132	32	13.12
WLS10136	36	16.59
WLS10140	40	20.56
WLS10144	44	24.78
WLS10148	48	29.55
WLS10152	52	34.69