



## Wire Rope Lifting Sling WLS-275

### Product information

**Standard steel wire rope construction: 6x36WS IWRC, 1960N/mm<sup>2</sup>**

**Design:** Master link in one end and eyehooks with safety latch in other ends, aluminum ferrule secured (mechanical spliced).

Load table at Technical Data -> Show table

Please specify the needed (working) length with your request.

Other rope construction and/or end-terminations such as top rings, shackles, hooks, etc.. possible on request. In that case, please contact us to discuss the possible options or specify it with your request.

Part code	Diameter mm	WLL ton	WLL 0-45° t	WLL 45-60° t
WLS27503	3	0.16	0.16	0.12
WLS27504	4	0.29	0.29	0.21
WLS27505	5	0.45	0.45	0.32
WLS27506	6	0.66	0.66	0.47
WLS27508	8	1.15	1.15	0.82
WLS27509	9	1.45	1.45	1.04
WLS27510	10	1.79	1.79	1.28
WLS27511	11	2.17	2.17	1.55

WLS27512	12	2.57	2.57	1.84
WLS27513	13	3.03	3.03	2.17
WLS27514	14	3.52	3.52	2.51
WLS27516	16	4.6	4.6	3.3
WLS27518	18	5.81	5.81	4.1
WLS27520	20	7.17	7.17	5.1
WLS27522	22	8.69	8.69	6.2
WLS27524	24	10.33	10.33	7.38
WLS27526	26	12.13	12.13	8.66
WLS27528	28	14.06	14.06	10.04
WLS27532	32	18.37	18.37	13.12
WLS27536	36	23.23	23.23	16.59
WLS27540	40	28.78	28.78	20.56
WLS27544	44	34.69	34.69	24.78

## Technical data