



## Wire Rope Lifting Sling WLS-373

### Product information

**Standard steel wire rope construction: 6x36WS IWRC, 1960N/mm<sup>2</sup>**

**Design:** Master link in one end and thimble in other ends, aluminum ferrule secured (mechanical spliced).

Load table at Technical Data -> Show table

Please specify the needed (working) length with your request.

Other rope construction and/or end-terminations such as top rings, shackles, hooks, etc.. possible on request. In that case, please contact us to discuss the possible options or specify it with your request.

Part code	Diameter mm	WLL ton	WLL 0-45° t	WLL 45-60° t
WLS37303	3	0.25	0.25	0.18
WLS37304	4	0.44	0.44	0.31
WLS37305	5	0.68	0.68	0.49
WLS37306	6	0.98	0.98	0.7
WLS37308	8	1.72	1.72	1.23
WLS37309	9	2.18	2.18	1.56
WLS37310	10	2.69	2.69	1.92
WLS37311	11	3.25	3.25	2.32

WLS37312	12	3.85	3.85	2.75
WLS37313	13	4.55	4.55	3.25
WLS37314	14	5.28	5.28	3.77
WLS37316	16	6.9	6.9	4.93
WLS37318	18	8.71	8.71	6.22
WLS37320	20	10.75	10.75	7.68
WLS37322	22	13.03	13.03	9.31
WLS37324	24	15.5	15.5	11.07
WLS37326	26	18.19	18.19	13
WLS37328	28	21.08	21.08	15.06
WLS37332	32	27.56	27.56	19.69
WLS37336	36	34.84	34.84	24.89
WLS37340	40	43.17	43.17	30.84
WLS37344	44	52.04	52.04	37.17
WLS37348	48	62.06	62.06	44.33
WLS37352	52	75.85	75.85	52.04

## Technical data