



# Wire Rope Lifting Sling WLS-000

## Product information

**Standard steel wire rope construction:** 6x36WS IWRC, 1960N/mm2\*  
(\*ø 3mm - ø 7mm rope construction: 6x19M WSC 1960 N/mm2)

**Design:** Endless, mechanically pressed with 2 alu. ferrules

Load table at Technical Data -> Show table

Please specify the needed (working) length with your request.

Other rope constructions possible on request. In that case, please contact us to discuss the possible options or specify it with your request.

**Note:** We recommend that the sling not is bent over a diameter less than 6 times the wire rope diameter without reducing the WLL.

Part code	Diameter mm	WLL ton
WLS00003	3	0.23
WLS00004	4	0.42
WLS00005	5	0.65
WLS00006	6	0.94
WLS00008	8	1.64
WLS00009	9	2.07
WLS00010	10	2.56
WLS00011	11	3.1

WLS00012	12	3.67
WLS00013	13	4.33
WLS00014	14	5.03
WLS00016	16	6.57
WLS00018	18	8.3
WLS00020	20	10.24
WLS00022	22	12.41
WLS00028	28	16.8
WLS00026	26	17.33
WLS00024	24	17.46
WLS00032	32	20.08
WLS00036	36	26.25
WLS00040	40	33.19
WLS00044	44	41.11
WLS00048	48	49.56
WLS00052	52	59.1

Technical data