

Short Link Lifting Chain POWERTEX PSLA

Product information



The PowerTex Grade 10 PSLA Lifting Chain is a reliable lifting chain intended for use in demanding industrial applications. This high-quality calibrated lifting chain ensures safety, durability, and compliance, making it the smart choice for your lifting needs.

Product benefits

- **Safe and tested:** each chain link is proof load tested to 2.5 times the Working Load Limit (WLL) before delivery. Additionally, each production batch undergoes rigorous testing to meet the minimum breaking force and elongation requirements, ensuring maximum safety in every use.
- **Long-lasting durability:** PSLA features a durable electrophoretic wet paint (E-coat) finish in blue, providing superior resistance to wear and corrosion. This ensures the chain remains reliable and functional even in demanding environments.
- **Exceptional ductility:** The chain offers great ductility, with a minimum elongation of 20% before failure, providing flexibility and resilience during lifting operations.
- **Accurate:** Each chain length is calibrated in the factory before delivery, ensuring accurate and consistent performance in every application.
- **Consistent Quality:** PSLA is manufactured using automatic chain welding machines, guaranteeing consistent quality and reliability, giving you peace of mind during critical lifting tasks.
- **Compliance and Certification:** The chains fulfill the Machinery Directive 2006/42/EC, ensuring they meet stringent safety and quality standards. Each box includes a 14-language 2.2 Certificate and EC/UKCA Declaration of Conformity, providing comprehensive documentation for compliance. [... Read more](#)

Material: Quenched and Tempered Alloy Steel of Grade 10 quality

Marking: According to standard, CE-marked, UKCA-marked, Factory symbol, Grade (10 or 100), Traceability batch marking

Temperature range: -40°C up to +200°C (without reduction in WLL)

Finish: Electrophoretic wet paint (E-coat) in blue


Standard: EN 818-2 (+ 25% WLL), AS 2321, ASTM A973/A973M

Safety factor: 4:1

Grade: 10

Short Link Lifting Chain POWERTEX PSLA

Blueprint



Technical data

Part code	Chain diameter mm	WLL ton	Min. breaking force kN	Pitch Length	Model	dmm mm	pmm mm	W1 min. mm	W2 max mm mm	Weight kg/m
PSLA-6-10	6	1.4	56.5	18	PSLA-6-10	6	18	7,8	22,2	0.8
PSLA-7-10	7	1.9	77	21	PSLA-7-10	7	21	9,1	25,9	1.2
PSLA-8-10	8	2.5	101	24	PSLA-8-10	8	24	10,4	29,6	1.5
PSLA-10-10	10	4	157	30	PSLA-10-10	10	30	13,0	37,0	2.3
PSLA-13-10	13	6.7	265	39	PSLA-13-10	13	39	16,9	48,1	3.9
PSLA-16-10	16	10	402	48	PSLA-16-10	16	48	20,8	59,2	5.8
PSLA-19-10	19	14	567	57	PSLA-19-10	19	57	24,7	70,3	8.4
PSLA-20-10	20	16	628	60	PSLA-20-10	20	60	26,0	74,0	8.9
PSLA-22-10	22	19	760	66	PSLA-22-10	22	66	28,6	81,4	11.4