MENNENS | Lifting Solutions Group
Axel Johnson International

Master Link MR POWERTEX (Reevable)

Product information



The POWERTEX Master Link MR Reevable is a Grade 10 pear-shaped master link with an integrated chain connector for assembling reevable collar chain slings. Used with an MR Reevable Master Link at each end of the chain, it creates a versatile lifting sling that is particularly suited to handling bundles of bars and pipes using a choke hitch or U-lift (also called basket).

Available for 8 mm up to 16 mm chain and from WLL 2.5t up to WLL 10t.

Best used for

- Reevable collar chain sling assemblies.
- Lifting bundles of bars and pipes in a choke hitch or U-lift.

Product benefits

- Pear-shaped design enables reevable collar chain sling configurations.
- Integrated chain connector simplifies sling assembly.
- Grade 10 design delivers 25% higher capacity than traditional Grade 8 components.
- Conforms to EN 1677 Parts 1, 2, 3, and 4 with 25% increased WLL.
- Each component is crack detection tested. Production samples are proof-load tested, and the design is factory-type tested.
- The design is fatigue tested to 20,000 cycles at 1.5 × WLL, with batch traceability and a POWERTEX 2.2 certificate.
- The components may also be used with a Grade 8 chain to EN 818-2. In such a case, the chain sling must be rated to Grade 8 in accordance with EN 818-4

... Read more

Marking: According to standard, POWERTEX + Model (MR-8-10) + traceability code.
Temperature range: -40°C up to +200°C without reduction in WLL
Finish: Powder painted in red
Standard: EN 1677-4 (+25% WLL) , AS 3776

Safety factor: 4:1
Grade: 10


Mennens Belgium
sales@mennensbelgium.be
+32 (0)3 253 23 23

© November 2026 - All Rights Reserved

MENNENS | Lifting Solutions Group
Axel Johnson International

Master Link MR POWERTEX (Reevable)

Blueprint



Technical data

Part code	Chain diameter mm	WLL ton	MBL ton	EWL mm	A mm	B mm	D mm	E mm	L mm	Ø mm mm	Weight kg
402100250940	8	2.5	10	106	10	32.8	45	87	139	15	0.5
402100400940	10	4	16	132	12	42	60	108	174	19	1
402100670940	13	6.7	26.8	177	16.5	55.5	66.5	137	228	22	1.8
402101000940	16	10	40	203	19	68	72	165	264	26	2.8

Mennens Belgium
sales@mennensbelgium.be
+32 (0)3 253 23 23

© November 2026 - All Rights Reserved