


Wall Mounted Jib Crane ASSISTENT AW

Product information



The wall-mounted slewing jib crane AW can be used as a versatile workplace crane featuring a capacity of up to 2,000 kg.

Due to its compact design, the crane features a maximum lifting height and is perfectly suitable for small and narrow operating rooms. Its optional electrical slewing gear (only partially available see Tab Technical Data), provides increased ease of use when operated in the higher capacity / outreach range. The wall-mounted slewing crane AW perfectly meets your requirements since its jib arm length can be adjusted individually.

Jib design: Low-profile.

Advantages:

- Comfortable and smooth slewing.
- Compact design, perfectly suited for small rooms
- Large effective lifting height

Optional:

- Suitable for outdoor use
- Broad range of fastening options provides for convenient installation
- Electrical slewing gear (only partially available check out the technical data tab)
- Column height and jib arm length can be adjusted to conditions
- Anchor sets for concrete floors or sets for steel constructions and machines.
- Hoist: Manual chain hoist or Electric hoist.
- Mechanical swing limitation for limiting the swing range (L or R).
- Locking system to secure the crane arm in various positions.
- Other finishes, corrosion category, RAL color and/or personalization of the crane in your corporate style, color(s), and labeling.

Contact our crane department for more information.

Material: Steel

Marking: According to standard, CE-marked

Finish: Standard: coating according to Corrosion category C2 (Ral 1007), nominal thickness 80 µm.

Standard: EN 13001

Part code

WLL

Length

AW0008-6000	0.08	6
AW0008-6500	0.08	6.5
AW0008-7000	0.08	7
AW0008-7500	0.08	7.5
AW0008-8000	0.08	8
AW0008-8500	0.08	8.5
AW0008-9000	0.08	9
AW0008-9500	0.08	9.5
AW0008-10000	0.08	10
AW0008-2000	0.08	2
AW0008-2500	0.08	2.5
AW0008-3000	0.08	3
AW0008-3500	0.08	3.5
AW0008-4000	0.08	4
AW0008-4500	0.08	4.5
AW0008-5000	0.08	5
AW0008-5500	0.08	5.5
AW0012-2000	0.125	2
AW0012-2500	0.125	2.5
AW0012-3000	0.125	3
AW0012-3500	0.125	3.5
AW0012-4000	0.125	4
AW0012-4500	0.125	4.5

AW0012-5000	0.125	5
AW0012-5500	0.125	5.5
AW0012-6000	0.125	6
AW0012-6500	0.125	6.5
AW0012-7000	0.125	7
AW0012-7500	0.125	7.5
AW0012-8000	0.125	8
AW0012-8500	0.125	8.5
AW0012-9000	0.125	9
AW0012-9500	0.125	9.5
AW0012-10000	0.125	10
AW0025-2000	0.25	2
AW0025-2500	0.25	2.5
AW0025-3000	0.25	3
AW0025-3500	0.25	3.5
AW0025-4000	0.25	4
AW0025-4500	0.25	4.5
AW0025-5000	0.25	5
AW0025-5500	0.25	5.5
AW0025-6000	0.25	6
AW0025-6500	0.25	6.5
AW0025-7000	0.25	7
AW0025-7500	0.25	7.5

AW0025-8000	0.25	8
AW0025-8500	0.25	8.5
AW0025-9000	0.25	9
AW0025-9500	0.25	9.5
AW0025-10000	0.25	10
AW0050-2000	0.5	2
AW0050-2500	0.5	2.5
AW0050-3000	0.5	3
AW0050-3500	0.5	3.5
AW0050-4000	0.5	4
AW0050-4500	0.5	4.5
AW0050-5000	0.5	5
AW0050-5500	0.5	5.5
AW0050-6000	0.5	6
AW0050-6500	0.5	6.5
AW0050-7000	0.5	7
AW0050-7500	0.5	7.5
AW0050-8000	0.5	8
AW0050-8500	0.5	8.5
AW0080-2000	0.8	2
AW0080-2500	0.8	2.5
AW0080-3000	0.8	3
AW0080-3500	0.8	3.5

AW0080-4000	0.8	4
AW0080-4500	0.8	4.5
AW0080-5000	0.8	5
AW0080-5500	0.8	5.5
AW0080-6000	0.8	6
AW0080-6500	0.8	6.5
AW0080-7000	0.8	7
AW0080-7500	0.8	7.5
AW0100-2000	1	2
AW0100-2500	1	2.5
AW0100-3000	1	3
AW0100-3500	1	3.5
AW0100-4000	1	4
AW0100-4500	1	4.5
AW0100-5000	1	5
AW0100-5500	1	5.5
AW0100-6000	1	6
AW0100-6500	1	6.5
AW0160-2000	1.6	2
AW0160-2500	1.6	2.5
AW0160-3000	1.6	3
AW0160-3500	1.6	3.5
AW0160-4000	1.6	4

AW0160-4500	1.6	4.5
AW0160-5000	1.6	5
AW0200-4000	2	4
AW0200-4500	2	4.5
AW0200-2000	2	2
AW0200-2500	2	2.5
AW0200-3000	2	3
AW0200-3500	2	3.5

Technical data

--