


## Wall Mounted Jib Crane PRAKTIKUS PW

### Product information



The wall-mounted slewing jib crane PW is our cost-effective basic slewing crane!

You can use it for simple operational tasks requiring a capacity of up to 2,000 kg. Its overbraced design and therefore lightweight jib arm enable especially easy slewing of the crane. The wall-mounted slewing crane PW perfectly meets your requirements for indoor and outdoor use since its jib arm length can be adjusted individually.

**Jib design:** Overbraced.

**Advantages:**

- Cost-effective
- Easy slewing
- Broad range of options and accessories available.

**Options and accessories:**

- Suitable for outdoor use
- Various mounting kits for concrete walls or steel structures.
- Trolley: manual or electric
- Hoist: manual or electric
- Mechanical slewing limitation
- Locking device to lock the crane arm in various positions.
- Various power supply options
- On-site installation
- Other finishes, RAL color and/or corrosion category or hot-dip galvanized (recommended for outdoor use).

**Marking:** According to standard, CE-marked

**Finish:** Standard: coating according to Corrosion category C2 (Ral 1007), nominal thickness 80 µm.

**Standard:** EN 13001

Part code	WLL ton	Length m
PW0008-6000	0.08	6

PW0008-2000	0.08	2
PW0008-2500	0.08	2.5
PW0008-3000	0.08	3
PW0008-3500	0.08	3.5
PW0008-4000	0.08	4
PW0008-4500	0.08	4.5
PW0008-5000	0.08	5
PW0008-5500	0.08	5.5
PW0012-2000	0.125	2
PW0012-2500	0.125	2.5
PW0012-3000	0.125	3
PW0012-3500	0.125	3.5
PW0012-4000	0.125	4
PW0012-4500	0.125	4.5
PW0012-5000	0.125	5
PW0012-5500	0.125	5.5
PW0012-6000	0.125	6
PW0025-2000	0.25	2
PW0025-2500	0.25	2.5
PW0025-3000	0.25	3
PW0025-3500	0.25	3.5
PW0025-4000	0.25	4
PW0025-4500	0.25	4.5

PW0025-5000	0.25	5
PW0025-5500	0.25	5.5
PW0025-6000	0.25	6
PW0025-6500	0.25	6.5
PW0025-7000	0.25	7
PW0050-2000	0.5	2
PW0050-2500	0.5	2.5
PW0050-3000	0.5	3
PW0050-3500	0.5	3.5
PW0050-4000	0.5	4
PW0050-4500	0.5	4.5
PW0050-5000	0.5	5
PW0050-5500	0.5	5.5
PW0050-6000	0.5	6
PW0080-2000	0.8	2
PW0080-2500	0.8	2.5
PW0080-3000	0.8	3
PW0080-3500	0.8	3.5
PW0080-4000	0.8	4
PW0080-4500	0.8	4.5
PW0080-5000	0.8	5
PW0080-5500	0.8	5.5
PW0080-6000	0.8	6

PW0100-2000	1	2
PW0100-2500	1	2.5
PW0100-3000	1	3
PW0100-3500	1	3.5
PW0100-4000	1	4
PW0100-4500	1	4.5
PW0100-5000	1	5
PW0160-2000	1.6	2
PW0160-2500	1.6	2.5
PW0160-3000	1.6	3
PW0160-3500	1.6	3.5
PW0200-2000	2	2
PW0200-2500	2	2.5
PW0200-3000	2	3

## Technical data

---