

Wall Mounted Jib Crane UNILIFT UW

Product information



The wall-mounted jib arm crane UW is a smooth-running crane with aluminium jib arm.

You can use it for easy, quick, and safe handling of small loads up to 500 kg; e.g. in logistics or automotive industry. Its overbraced design and therefore lightweight aluminium jib arm enable especially easy slewing of the crane. Thanks to the good running qualities of the internal push trolley, the optional hoist moves quite easily.

Jib design: Overbraced

Advantages:

- Light jib arm
- Easy slewing
- Smooth running trolley
- Ergonomic handling

Options and accessories:

- Various mounting kits for concrete walls or steel structures.
- Hoist: manual or electric
- Mechanical slewing limitation
- Locking device to lock the crane arm in various positions.
- On-site installation
- Other finishes, RAL color and/or corrosion category or hot-dip galvanized (recommended for outdoor use).

... [Read more](#)

Material: Steel - Aluminium

Marking: According to standard, CE-marked

Standard: EN 13001

Wall Mounted Jib Crane UNILIFT UW

Technical data

Part code	WLL ton	Length m
UW0008-1900	0.08	1.9
UW0008-2400	0.08	2.4
UW0008-2900	0.08	2.9
UW0008-3400	0.08	3.4
UW0008-3900	0.08	3.9
UW0008-4400	0.08	4.4
UW0008-4900	0.08	4.9
UW0008-5400	0.08	5.4
UW0008-5900	0.08	5.9
UW0012-1900	0.125	1.9
UW0012-2400	0.125	2.4
UW0012-2900	0.125	2.9
UW0012-3400	0.125	3.4
UW0012-3900	0.125	3.9
UW0012-4400	0.125	4.4
UW0012-4900	0.125	4.9
UW0012-5400	0.125	5.4
UW0012-5900	0.125	5.9
UW0025-1900	0.25	1.9
UW0025-2400	0.25	2.4
UW0025-2900	0.25	2.9
UW0025-3400	0.25	3.4
UW0025-3900	0.25	3.9
UW0025-4400	0.25	4.4
UW0025-4900	0.25	4.9
UW0025-5400	0.25	5.4
UW0025-5900	0.25	5.9
UW0032-1900	0.32	1.9
UW0032-2400	0.32	2.4
UW0032-2900	0.32	2.9
UW0032-3400	0.32	3.4

Wall Mounted Jib Crane UNILIFT UW

Technical data

Part code	WLL ton	Length m
UW0032-3900	0.32	3.9
UW0032-4400	0.32	4.4
UW0032-4900	0.32	4.9
UW0032-5400	0.32	5.4
UW0050-1900	0.5	1.9
UW0050-2400	0.5	2.4
UW0050-2900	0.5	2.9
UW0050-3400	0.5	3.4
UW0050-3900	0.5	3.9
UW0050-4400	0.5	4.4