

# Mobile Jib Crane MOBILUS MOB-AS

## Product information



The MOB-AS is a mobile column slewing crane with a rotation range of 270°. Thanks to its compact design, this slewing crane is extremely suitable for small and narrow workshops or workspaces. The crane offers various options for relocation, such as a mobile base manual movable or with forklift connector bar, fork lift truck pockets, or lifting eyes for movement with an overhead crane (all optional).

### Slewing Crane Custom Configuration:

The mobile crane MOB-AS can be perfectly configured to your specific requirements. The column height and the length of the lifting arm can be adjusted to size. Thanks to the integrated counterweight in the crane base, the MOB-AS is completely independent and does not require anchoring to the foundation or drilling into the concrete floor. Because the crane is movable, it is standard equipped with a locking device for securing the crane arm, which is mandatory for movable slewing cranes.

### Standard features:

- Capacity range: 125 - 500 kg
- Outreach: 2000 - 6000 mm
- slewing range: 270°
- Crane height: 2120 - 5250 mm
- Height under crane arm: 1800 - 5000 mm

**Crane arm Design:** The crane arm is designed with an I-profile and under bracing, ensuring a robust and reliable construction.

### Advantages:

- No attachment required:
- The crane is completely independent thanks to the integrated counterweight.
- Modular design: The MOBILUS base can be combined with various other MOB crane types.
- Easy and quick to relocate: The crane can be easily moved to different locations within your workspace.

### Options and Accessories:

- Trolley: Available in manual or electric versions.
- Hoist: Choice of manual chain hoist or electric hoist.
- Power supply systems: Various options available.
- Mechanical swing limit: For limiting the swing range (left or right).
- Personalization: Other finishes, RAL colors and/or personalization of the crane in your house style, color(s), and signage.

At Mennens, we strive for the highest quality and reliability in our products. The MOB-AS mobile column slewing crane is designed and manufactured according to the strictest standards, with attention to detail and safety. Our years of experience and expertise in the industry ensure that you receive a product that meets your expectations and requirements. Trust Mennens for your lifting and hoisting solutions. For

more information or a custom quote, please contact us via our contact form, our slewing crane configurator, or the shopping cart. Our experts are happy to assist you!

**Marking:** According to standard, CE-marked

**Standard:** EN 13001

**Note:** It's not allowed to move the crane under load.

Part code	WLL ton	Length m
MOB-AS0012-2000	0.125	2
MOB-AS0012-2500	0.125	2.5
MOB-AS0012-3000	0.125	3
MOB-AS0012-3500	0.125	3.5
MOB-AS0012-4000	0.125	4
MOB-AS0012-4500	0.125	4.5
MOB-AS0012-5000	0.125	5
MOB-AS0012-5500	0.125	5.5
MOB-AS0012-6000	0.125	6
MOB-AS0025-2000	0.25	2
MOB-AS0025-2500	0.25	2.5
MOB-AS0025-3000	0.25	3
MOB-AS0025-3500	0.25	3.5
MOB-AS0025-4000	0.25	4
MOB-AS0025-4500	0.25	4.5
MOB-AS0025-5000	0.25	5
MOB-AS0032-2000	0.32	2

MOB-AS0032-2500	0.32	2.5
MOB-AS0032-3000	0.32	3
MOB-AS0032-3500	0.32	3.5
MOB-AS0032-4000	0.32	4
MOB-AS0032-4500	0.32	4.5
MOB-AS0050-2000	0.5	2
MOB-AS0050-2500	0.5	2.5
MOB-AS0050-3000	0.5	3

## Technical data

### CAPACITY RANGE

		Outreach [m]								
		2	2.5	3	3.5	4	4.5	5	5.5	6
Capacity [kg]	125	■	■	■	■	■	■	■	□	□
	250	■	■	■	■	□	□	□		
	320	■	■	□	□	□	□			
	500	■	□	□						

■ Crane base either 1175×1040 mm or 1360×1240 mm □ Crane base 1360×1240 mm