

Fall Arrest Block IKAR Flexible HWB 2,0 DWX

Product information



Fall arrest block double with webbing and swivel suspension, which prevents the webbing from twisting. Integrated energy-absorber and retractable lanyard.

Seawater-resistant aluminum housing with retractable lanyard made of almost indestructible Dyneema® webbing.

Approved for vertical and horizontal use.

Edge tested: Tested at sharp edges, $R \geq 0,5 \text{ mm}$ (CNB/P/11.060 2008 sharp edge Type A)

Carabiner: IKV 32 with opening width 66 mm in the bottom

Shock absorbtion: Max. shock impact $< 4 \text{ kN}$.

[... Read more](#)

Material: Housing: aluminium, webbing: Dyneema®

Marking: According to standard

Temperature range: -40°C up to $+50^{\circ}\text{C}$

Finish: Blue painted

Standard: EN 360

Fall Arrest Block IKAR Flexible HWB 2,0 DWX

Blueprint



Technical data

| Part code | Code | Max. number of persons | Length m | Max load kg | B mm | L mm | T mm | Weight kg |
|-----------------|--------------|------------------------|----------|-------------|------|------|------|-----------|
| 19.0741-HWB2DWX | HWB 2,0 DW X | 1 | 2.5 | 136 | 170 | 425 | 67 | 2.2 |