

GL300 Cable Grip open with thimbles - lace up

Product information

General: Tool for mounting of wire ropes.

Design: Open with two thimbles – lace up version.

Also available in special editions in larger sizes and stainless material.

Material: Galvanized steelwire 1960N/mm²



| Part code | Rope Ø range mm | Length mm | Max. pullingforce kN | Thimble Ø mm |
|-------------------|--------------------|--------------|-------------------------|-----------------|
| 10.15KBZ310/1250 | 8-15 | 1,250 | 6.2 | 18 |
| 10.15KBZ315/1250 | 15-20 | 1,250 | 12.8 | 18 |
| 10.15KBZ320/1250 | 20-30 | 1,250 | 16 | 18 |
| 10.15KBZ330/1250 | 30-40 | 1,250 | 19.2 | 18 |
| 10.15KBZ340/1250 | 40-50 | 1,250 | 22.4 | 18 |
| 10.15KBZ350/1500 | 50-60 | 1,500 | 37.4 | 20 |
| 10.15KBZ360/1500 | 60-70 | 1,500 | 49.9 | 24 |
| 10.15KBZ370/1500 | 70-80 | 1,500 | 49.9 | 24 |
| 10.15KBZ380/1500 | 80-90 | 1,500 | 56.2 | 24 |
| 10.15KBZ390/1500 | 90-100 | 1,500 | 62.4 | 24 |
| 10.15KBZ3100/1500 | 100-115 | 1,500 | 62.4 | 24 |
| 10.15KBZ3115/1500 | 115-130 | 1,500 | 74.8 | 40 |
| 10.15KBZ3130/1500 | 130-150 | 1,500 | 74.8 | 40 |
| 10.15KBZ3150/1500 | 150-180 | 1,500 | 87.3 | 45 |
| 10.15KBZ3180/2000 | 180-210 | 2,000 | 99.8 | 45 |
| 10.15KBZ3210/2000 | 210-240 | 2,000 | 99.8 | 45 |
| 10.15KBZ3250/2000 | 240-300 | 2,000 | 124.8 | 45 |