

## GL400 Cable Grip two side open

### Product information

**General:** Tool for mounting of wire ropes.

**Design:** Two sides open

Also available in special editions in larger sizes and stainless material.

**Material:** Galvanized steelwire 1960N/mm<sup>2</sup>



Part code	Rope Ø range mm	Length mm	Max. pullingforce kN
10.15KBZ406/1500	6-8	1,500	3.3
10.15KBZ406VS/1500	6-8	1,500	4.9
10.15KBZ408/1500	8-10	1,500	4.6
10.15KBZ408VS/1500	8-10	1,500	6.9
10.15KBZ410/1500	8-15	1,500	6.2
10.15KBZ410VS/1500	8-15	1,500	9.4
10.15KBZ415/1500	15-20	1,500	12.8
10.15KBZ415VS/1500	15-20	1,500	19.2

10.15KBZ420/1500	20-30	1,500	16
10.15KBZ420VS/1500	20-30	1,500	24
10.15KBZ430/1500	30-40	1,500	19.2
10.15KBZ430VS/1500	30-40	1,500	28.8
10.15KBZ440/1500	40-50	1,500	22.4
10.15KBZ440VS/1500	40-50	1,500	33.6
10.15KBZ450/1500	50-60	1,500	37.4
10.15KBZ450VS/1500	50-60	1,500	56.2
10.15KBZ460/1500	60-70	1,500	49.9
10.15KBZ460VS/1500	60-70	1,500	74.9
10.15KBZ470/1500	70-80	1,500	49.9
10.15KBZ470VS/1500	70-80	1,500	74.9
10.15KBZ480/1500	80-90	1,500	56.2
10.15KBZ480VS/1500	80-90	1,500	84.2
10.15KBZ490/1500	90-100	1,500	62.4
10.15KBZ490VS/1500	90-100	1,500	93.6
10.15KBZ4100/1500	100-115	1,500	62.4
10.15KBZ4100VS/1500	100-115	1,500	93.6
10.15KBZ4115/1500	115-130	1,500	74.8
10.15KBZ4115VS/1500	115-130	1,500	112.2