

## Lifting Beam Type H

### Product information



### CERTEX

This type of lifting beam cannot be adjusted and is designed for direct attachment with the crane hook in the central lifting eye. The lifting beam is designed with one attachment point in each corner and is based on lifting assignments in all four points. Other lengths and working loads can be manufactured upon request.

**Design:** Lightweight welded pipe beam construction providing good torsional stiffness.

**Proof load:** Usually 1,5 x WLL.

**Material:** Hollow beam and plate manufactured with high-strength structural steel.

**Marking:** Working load limit (WLL), CE marking, manufacturer, serial number, year of manufacturing, etc.

**Finish:** Yellow painted. Other treatments available on request.

**Note:** Top sling, separate slings and other accessories to be ordered separately.

Part code	Code	WLL	H mm	L1 mm	L2 mm	Weight kg
13.3564-10051500	H-0,5/2-1,5	0.5	255	2,000	1,500	80
13.3564-10052000	H-0,5/3-2	0.5	255	3,000	2,000	109
13.3564-10052500	H-0,5/4-2,5	0.5	255	4,000	2,500	152
13.3564-10151500	H-1,5/2-1,5	1.5	310	2,000	1,500	102
13.3564-10152000	H-1,5/3-2	1.5	310	3,000	2,000	139
13.3564-10152500	H-1,5/4-2,5	1.5	310	4,000	2,500	216
13.3564-10301500	H-3/2-1,5	3	395	2,000	1,500	131
13.3564-10302000	H-3/3-2	3	395	3,000	2,000	185
13.3564-10302500	H-3/4-2,5	3	395	4,000	2,500	263
13.3564-10501500	H-5/2-1,5	5	440	2,000	1,500	193
13.3564-10502000	H-5/3-2	5	440	3,000	2,000	275
13.3564-10502500	H-5/4-2,5	5	440	4,000	2,500	388
13.3564-10801500	H-8/2-1,5	8	555	2,000	1,500	326
13.3564-10802000	H-8/3-2	8	555	3,000	2,000	422
13.3564-10802500	H-8/4-2,5	8	555	4,000	2,500	565
13.3564-11001500	H-10/2-1,5	10	720	2,000	1,500	502
13.3564-11002000	H-10/3-2	10	720	3,000	2,000	647
13.3564-11002500	H-10/4-2,5	10	720	4,000	2,500	793

## Blueprint

