

Lifting Beam Type H-SB

Product information



CERTEX

This type of lifting beam has adjustable attachment points in one direction via a cam beam and is based on lifting in four points. The lifting beam is designed for direct attachment with the crane hook in the central lifting eye. The attachment points are designed as oval rings, which makes it possible to use for example a 2-part sling. Other lengths and working loads can be manufactured upon request.

Design: Lightweight welded beam construction providing good torsional stiffness.

Proof load: Usualley 1,5 x WLL.

Material: Beam and plate of high-strength structural steel.

Marking: Working load limit (WLL), CE marking, manufacturer, serial number, year of manufacturing, etc.

Finish: Yellow painted. Other treatments available on request.

Note: Top sling, separate slings and other accessories to be ordered separately.

Part code	Code	WLL ton	H mm	L1 mm	L2 mm	Weight kg
13.3564-20051500	H-SB-0,5/2-1,5	0.5	280	2,000	1,500	97
13.3564-20052000	H-SB-0,5/3-2	0.5	280	3,000	2,000	143
13.3564-20052500	H-SB-0,5/4-2,5	0.5	280	4,000	2,500	173
13.3564-20151500	H-SB-1,5/2-1,5	1.5	330	2,000	1,500	135
13.3564-20152000	H-SB-1,5/3-2	1.5	330	3,000	2,000	178
13.3564-20152500	H-SB-1,5/4-2,5	1.5	330	4,000	2,500	256
13.3564-20301500	H-SB-3/2-1,5	3	415	2,000	1,500	165
13.3564-20302000	H-SB-3/3-2	3	415	3,000	2,000	224
13.3564-20302500	H-SB-3/4-2,5	3	415	4,000	2,500	302
13.3564-20501500	H-SB-5/2-1,5	5	455	2,000	1,500	229
13.3564-20502000	H-SB-5/3-2	5	455	3,000	2,000	320
13.3564-20502500	H-SB-5/4-2,5	5	455	4,000	2,500	428
13.3564-20801500	H-SB-8/2-1,5	8	595	2,000	1,500	422
13.3564-20802000	H-SB-8/3-2	8	595	3,000	2,000	524
13.3564-20802500	H-SB-8/4-2,5	8	595	4,000	2,500	667
13.3564-21001500	H-SB10/2-1,5	10	760	2,000	1,500	609
13.3564-21002000	H-SB-10/3-2	10	760	3,000	2,000	760
13.3564-21002500	H-SB10/4-2,5	10	760	4,000	2,500	906

Blueprint

