

Lifting Beam Type K



Product information



This type of lifting beam is characterized by adjustable attachments via a cam beam and it is designed for direct attachment to the crane hook in the central lifting eye. The attachment points are designed as oval rings, which makes it possible to use for example a 2-part sling. Other lengths and working loads can be manufactured upon request.

Design: Lightweight welded pipe beam construction providing good torsional stiffness.

Proof load: Usually 1,5 x WLL.

Material: Hollow beam and plate manufactured with high-strength structural steel.

Marking: Working load limit (WLL), CE marking, manufacturer, serial number, year of manufacturing, etc.

Finish: Yellow painted. Other treatments available on request.

Note: Top sling, separate slings and other accessories to be ordered separately.

Safety factor: 1,5 x WLL

Part code	Code	WLL ton	B,	H,	L min. mm	L max. mm	Weight kg
13.3562-0051500	K-0,5/1,5	0.5	95	250	750	1,500	28
13.3562-0052000	K-0,5/2	0.5	95	250	800	2,000	34
13.3562-0052500	K-0,5/2,5	0.5	95	250	1,300	2,500	38
13.3562-0053000	K-0,5/3	0.5	95	250	1,350	3,000	58
13.3562-0053500	K-0,5/3,5	0.5	120	280	1,850	3,500	72
13.3562-0054000	K-0,5/4	0.5	120	280	1,900	4,000	81
13.3562-0055000	K-0,5/5	0.5	120	280	2,450	5,000	139
13.3562-0056000	K-0,5/6	0.5	140	330	3,000	6,000	172

13.3562-0101500	K-1/1,5	1	120	280	750	1,500	32
13.3562-0102000	K-1/2	1	120	280	800	2,000	48
13.3562-0102500	K-1/2,5	1	120	280	1,300	2,500	56
13.3562-0103000	K-1/3	1	120	280	1,350	3,000	65
13.3562-0103500	K-1/3,5	1	120	280	1,850	3,500	101
13.3562-0104000	K-1/4	1	140	330	1,900	4,000	146
13.3562-0106000	K-1/6	1	156	415	3,000	6,000	169
13.3562-0105000	K-1/5	1	140	330	2,450	5,000	177
13.3562-0201500	K-2/1,5	2	140	330	750	1,500	48
13.3562-0202000	K-2/2	2	140	330	800	2,000	56
13.3562-0202500	K-2/2,5	2	140	330	1,300	2,500	74
13.3562-0203000	K-2/3	2	140	330	1,350	3,000	98
13.3562-0203500	K-2/3,5	2	140	330	1,850	3,500	132
13.3562-0204000	K-2/4	2	156	415	1,900	4,000	135
13.3562-0205000	K-2/5	2	156	415	2,450	5,000	207
13.3562-0206000	K-2/6	2	156	415	3,000	6,000	253
13.3562-0301500	K-3/1,5	3	145	417	600	3,000	58
13.3562-0302000	K-3/2	3	156	415	800	2,000	74
13.3562-0303000	K-3/3	3	156	415	1,350	3,000	115
13.3562-0304000	K-3/4	3	156	415	1,900	4,000	174
13.3562-0305000	K-3/5	3	106	455	2,450	5,000	246
13.3562-0306000	K-3/6	3	250	595	3,000	6,000	408
13.3562-0502000	K-5/2	5	106	455	800	2,000	106

13.3562-0503000	K-5/3	5	106	455	1,350	3,000	165
13.3562-0504000	K-5/4	5	106	455	1,900	4,000	245
13.3562-0505000	K-5/5	5	250	595	2,450	5,000	258
13.3562-0506000	K-5/6	5	250	595	3,000	6,000	409
13.3562-0802000	K-8/2	8	106	455	800	2,000	123
13.3562-0803000	K-8/3	8	250	595	1,350	3,000	250
13.3562-0804000	K-8/4	8	250	595	1,900	4,000	352
13.3562-0805000	K-8/5	8	250	595	2,450	5,000	495
13.3562-0806000	K-8/6	8	280	760	3,000	6,000	600
13.3562-1002000	K-10/2	10	250	595	800	2,000	266
13.3562-1003000	K-10/3	10	250	595	1,350	3,000	330
13.3562-1004000	K-10/4	10	250	595	1,900	4,000	383
13.3562-1005000	K-10/5	10	280	760	2,450	5,000	522
13.3562-1006000	K-10/6	10	280	760	3,000	6,000	704
13.3562-1604000	K-16/4	16	280	760	1,900	4,000	517
13.3562-1605000	K-16/5	16	330	825	2,450	5,000	741

Blueprint

