

Lifting Beam Type LO

Product information



This type of lifting beam functions primarily as a spreader beam meaning that a 2-part sling must be used between the crane hook and the lifting beam. The lifting beam is designed with 2x3 attachment points, which makes it possible to have several different types of attachments mounted on the lifting beam at the same time. Other lengths and working loads can be manufactured upon request.

Design: Lightweight welded pipe beam construction providing good torsional stiffness.

Proof load: Usually 1,5 x WLL.

Marking: Working load limit (WLL), CE marking, manufacturer, serial number, year of manufacturing, etc.

Finish: Yellow painted. Other treatments available on request.

Note: Top sling, separate slings and other accessories to be ordered separately.



Part code	Code	WLL 90° ton	WLL 120° ton	B,	L	L min. mm	L max. mm	Weight kg
13.4063-0051500	LO-0,5/1,5	0.5	0.3	50	1,500	1,300	1,700	12
13.4063-0052000	LO-0,5/2	0.5	0.3	50	2,000	1,800	2,200	14
13.4063-0052500	LO-0,5/2,5	0.5	0.3	50	2,500	2,300	2,700	16
13.4063-0053000	LO-0,5/3	0.5	0.3	50	3,000	2,800	3,200	19
13.4063-0101500	LO-1/1,5	1	0.7	70	1,500	1,300	1,700	20
13.4063-0053500	LO-0,5/3,5	0.5	0.3	50	3,500	3,300	3,700	21
13.4063-0102000	LO-1/2	1	0.7	70	2,000	1,800	2,200	24
13.4063-0102500	LO-1/2,5	1	0.7	70	2,500	2,300	2,700	28

13.4063-0201500	LO-2/1,5	2	1.2	90	1,500	1,300	1,700	31
13.4063-0103000	LO-1/3	1	0.7	70	3,000	2,800	3,200	32
13.4063-0103500	LO-1/3,5	1	0.7	70	3,500	3,300	3,700	36
13.4063-0202000	LO-2/2	2	1.2	90	2,000	1,800	2,200	37
13.4063-0054000	LO-0,5/4	0.5	0.3	70	4,000	3,800	4,200	40
13.4063-0202500	LO-2/2,5	2	1.2	90	2,500	2,300	2,700	43
13.4063-0055000	LO-0,5/5	0.5	0.3	70	5,000	4,800	5,200	48
13.4063-0203000	LO-2/3	2	1.2	90	3,000	2,800	3,200	49
13.4063-0302000	LO-3/2	3	2	120	2,000	1,800	2,200	52
13.4063-0203500	LO-2/3,5	2	1.2	90	3,500	3,300	3,700	55
13.4063-0056000	LO-0,5/6	0.5	0.3	70	6,000	5,800	6,200	56
13.4063-0104000	LO-1/4	1	0.7	90	4,000	3,800	4,200	61
13.4063-0502000	LO-5/2	5	3	120	2,000	1,800	2,200	68
13.4063-0303000	LO-3/3	3	2	120	3,000	2,800	3,200	69
13.4063-0105000	LO-1/5	1	0.7	90	5,000	4,800	5,200	73
13.4063-0802000	LO-8/2	8	5	140	2,000	1,800	2,200	83
13.4063-0106000	LO-1/6	1	0.7	90	6,000	5,800	6,200	85
13.4063-0204000	LO-2/4	2	1.2	90	4,000	3,800	4,200	87
13.4063-0304000	LO-3/4	3	2	120	4,000	3,800	4,200	87
13.4063-0503000	LO-5/3	5	3	120	3,000	2,800	3,200	89
13.4063-1002000	LO-10/2	10	6	140	2,000	1,800	2,200	99
13.4063-0205000	LO-2/5	2	1.2	100	5,000	4,800	5,200	105
13.4063-0803000	LO-8/3	8	5	140	3,000	2,800	3,200	105

13.4063-0504000	LO-5/4	5	3	120	4,000	3,800	4,200	110
13.4063-0206000	LO-2/6	2	1.2	100	6,000	5,800	6,200	123
13.4063-1003000	LO-10/3	10	6	150	3,000	2,800	3,200	123
13.4063-0804000	LO-8/4	8	5	140	4,000	3,800	4,200	128
13.4063-0305000	LO-3/5	3	2	140	5,000	4,800	5,200	131
13.4063-1004000	LO-10/4	10	6	150	4,000	3,800	4,200	147
13.4063-0505000	LO-5/5	5	3	120	5,000	4,800	5,200	151
13.4063-0306000	LO-3/6	3	2	140	6,000	5,800	6,200	152
13.4063-0805000	LO-8/5	8	5	140	5,000	4,800	5,200	171
13.4063-0506000	LO-5/6	5	3	120	6,000	5,800	6,200	173
13.4063-0806000	LO-8/6	8	5	140	6,000	5,800	6,200	195
13.4063-1604000	LO-16/4	16	10	200	4,000	3,800	4,200	205
13.4063-1005000	LO-10/5	10	6	150	5,000	4,800	5,200	206
13.4063-1605000	LO-16/5	16	10	200	5,000	4,800	5,200	226
13.4063-1006000	LO-10/6	10	6	150	6,000	5,800	6,200	233
13.4063-1606000	LO-16/6	16	10	200	6,000	5,800	6,200	256

Blueprint

