Lifting Solutions Group
Axel Johnson International

MR multirailclamp

Product information



General:
The MR Multi-rail grabs have been designed to facilitate the fastbulk handling of a specific rail section (details to be advised at time of order). Rails are locked onto the clamp by swivelling feet that locate under the rail-head and top clamp body that rotates in a cam actionpressing a hard rubber lined horizontal beam onto the top of the rail-head. The rubber lined contact beam prevents marking or damage to the rail-head.Two clamps are recommended at centres of 50% to 60% of raillength for rails up to 20 mtr long. For rails longer than 20mtr, three clamps at centre distance between outer clamps of 65% to 75%of rail length must be used. (NB. Clamp must be within rated WLL). Rails to be lifted must be stacked with bottom flange toes touching. All rails must be of the same rail section size.

... *Read more*

Mennens Belgium
sales@mennensbelgium.be
+32 (0)3 253 23 23

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

MR multirailclamp

Technical data

Part code	WLL ton	Type	Number of rails	Weight kg
502150000000110	5	MR3	3	84
502150000000114	5	MR4	4	108
502150000000115	5	MR5	5	132
502160000000110	6	MR6	6	156
502170000000110	7	MR7	7	180
502180000000110	8	MR8	8	204
502110000000110	10	MR10	10	252
502112000000110	12	MR12	12	300

Mennens Belgium
sales@mennensbelgium.be
+32 (0)3 253 23 23

© November 2026 - All Rights Reserved