

## Stainless Steel Hand Winch MR500-5000

### Product information



This stainless steel hand winch is corrosion resistant and is made of stainless steel 316. The worm gear winch is IP54 classified which means that it is resistant to splashing water and dust on the inside. This makes the winch resistant to the toughest conditions and has a very high corrosion resistance rating.

- winch suitable for lifting and pulling in compliance with EN13157
- static safety factor 4
- load pressure brake with double ratchet system for safe stable hold of the load
- closed gearbox to protect against environmental influence – protection classification IP54
- cable outlet upwards, downwards or at rear
- adjustable crank
- suitable for wall and (optional) floor mounting
- stainless steel 316 body, drum, crank and all outgoing parts
- corrosion resistant

#### Options:

- grooved drum (GD)
- 2 drum compartment (2D) or multiple up to 8 (XD)
- suitable for floor mounting (FM)
- suitable for Dyneema rope (DY)
- pressure roller (PR)
- ATEX certified zone 2 and 22 (EX)
- CE II 3G Ex IIC T4 Gc, -20°C < T amb < +70°C

[... Read more](#)

**Material:** Stainless steel AISI 316

**Marking:** According to standard


**Standard:** EN 13157

**Note:** Steel, stainless steel or fiber ropes must be ordered separately

**Safety factor:** 4:1

## Stainless Steel Hand Winch MR500-5000

### Blueprint



### Technical data

| WLL ton | Model      | Rope Ø mm | Rope capacity m | Capacity top layer kg | Weight kg |
|---------|------------|-----------|-----------------|-----------------------|-----------|
| 0.5     | MR500 SST  | 6         | 78.2            | 224                   | 16        |
| 1.5     | MR1500 SST | 10        | 41.3            | 846                   | 30        |
| 3       | MR3000 SST | 14        | 68.7            | 1,667                 | 104       |
| 5       | MR5000 SST | 18        | 42.9            | 3,276                 | 135       |