



Pillar jib crane, overbraced, 180°, movable: PFT MOB

Product information

Appropriate for an indoor or outdoor use, the beam of the PMT is built on an I beam profile. Its light weight gives it great flexibility for rotations of 270°. The structure of this jib crane is suitable for the optional installation of a hoist motor direction.

This jib crane is mounted on a movable concrete block provided. Displacement can be done by traveling crane (transport ring) or by forklift.

A full range of accessories is available.

Options

- Hoist power supply cable.
- Lockable main switch.
- Rotation slowing device.
- Rotation stops to weld onto the assembly, or adjustable.
- Single- or multipositions rotation lock
- Outdoor use.
- Hot dip galvanizing (contact us).
- Electric or manual hoist.

| Part Code | WLL ton | Cap. kg | Span m 2,0 | Span m 2,5 | Span m 3,0 | Span m 3,5 | Span m 4,0 | Span m 4,5 | Span m 5,0 | Span m 5,5 | Span m 6,0 |
|---------------|------------|------------|---------------|---------------|---------------|---------------|---------------|---------------|---------------|---------------|---------------|
| 6025PFTMOB015 | 0.15 | 150 | • | • | • | • | • | • | • | • | • |
| 6025PFTMOB025 | 0.25 | 250 | • | • | • | • | • | • | • | - | - |
| 6025PFTMOB050 | 0.5 | 500 | • | • | • | - | - | - | - | - | - |